
rcrm 310U-5 (November 1983) (Formerly 9-331)	UNITED STATES DEPARTMENT OF THE INTER BUREAU OF LAND MANAGEMEN		n re 5. i	Budget Burcau Expires August EASE DESIGNATION	31, 1985
(Do not use this	IDRY NOTICES AND REPORTS form for proposals to drill or to deepen or plug Use "APPLICATION FOR PERMIT." for such		6. 1	F INDIAN, ALLOTTE	
OIL GAS WELL 2. NAME OF OPERATOR	E OTHER	91 JAN -7 PN 2	17	NIT AGREEMENT NA	
Morgan Richa	NM F	8. FARM OR LEASE NAME Federal 32-17 9. WELL NO.			
P. O. Box 19 4. LOCATION OF WELL (1) See also space 17 bel At surface	10.	#2 10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal			
,	o' FSL, 1340' FWL (NESW)		1	SEC., T., R., M., OR E SURVEY OR ARMA 7, T28N, R8	W NMPM
14. PERMIT NO.	15 BLEVATIONS (Show whether D		1	county or Parise an Juan	13. STATE NM
rest water shut-of practure treat siloot or acidize repair well (Other) 17. Describe proposed of proposed work. If nent to this work.) Pressure to 54 jts of 4 PBD of 2210 sodium meta	ABANDON* CHANGE PLANS COMPLETED OPERATIONS (Clearly state all pertine well is directionally drilled, give subsurface local state and 1/2", 10.5# and 11.6#, J-55 O' KB. Cemented with 150 sx (asilicate and 1/4 #/sk cello is containing 2% CaCl and 1/4 #/	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) Producti (Noth: Report re (Completion or Re nt details, and give pertinent of ations and measured and true v to 1500 psi for 30 casing, Casing la (581 cf) of Class B flakes, Tailed wit	on Casi sults of mu completion lates, includentical depti min—he nded at contai h 150 s	EPORT OF: REPAIRING V. ALTERING C. ABANDONMER ING REPORT Initiple completion Report and Log for Iting estimated dat thas for all markers Eld OK. Rar 2250' KB. ning 3% x (177 cf)	on Well rm.) e of starting any and zones perti-
		RECEIVE			



18. I hereby certify that the foregoing is true and correct SIGNED Delucuthal	TITLE Agent	DATE Jan 7, 1991
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	ACCEPTED FOR RECORD
•		FEB 0 5 1991

*See Instructions on Reverse Side