Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RE	CE	١V	ED	
	Q!	1.6		

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

Lease Designation and Serial No.

NM-03380

	Lease	Designation	and	Serial	No.
--	-------	-------------	-----	--------	-----

6. If Indian, Allottee or Tribe Name

			_
UNDRY NOTICES AN	D REPORTS C	ON WELLS	

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

7. If Unit or CA, Agreement Designation

SUBMI	IN TRIPLICATE	E1
1. Type of Well Oil Well X Gas Well Other		Florance 3. Well Name and No.
2. Name of Operator Cross Timbers Operating Compa	iny	Florance #70 D. API Well No.
3. Address and Telephone No. 6001 Highway 64, Farmington,	NM 87401 505/632-5200	30-045-29718 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey I 2025' FSL & 2035' FEL (Surface	L	Fruitland Coal 11. County or Parish, State
1189' FSL & 1009' FEL (BHL)*	The state of the s	San Juan Co., NM
TYPE OF SUBMISSION	s) TO INDICATE NATURE OF NOTICE, REPORT	, ON OTHER DATA
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
X Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing Other Running 4-1/2" casing	Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and true vertices) 	Il pertinent details, and give pertinent dates, including estimated date of starting areal depths for all markers and zones pertinent to this work.)*	ny proposed work. If well is directionally drilled,

Drilled 7-7/8" hole to 3385', TD, 11/21/98. RU & ran new 4-1/2", 10.5#, J-55, STC casing & set @ 3383'. RU Dowell & cemented w/365 sx Cl B cement w/3% D79 & 1/4#/sx Celloflake followed w/200 sx Cl B cement w/2% CaCl & 1/4#/sx Celloflake. Displaced w/53 bbls fresh water. Plug down @ 4:00 a.m., 11/22/98 w/1350 psig (550 psig over final displacement pressure). Float held OK. Circulated 78 sx cement to surface. BOP. Set slips and cut off casing. Released rig @ 6:00 a.m., 11/22/98. WOC.

* Actual "as drilled" BHL location.

I hereby certify that the foregoing is true and correct Signed Bobly Smith	Title _	Drilling/Operations Manager	Date 11/30/98
This space for Federal or State office use) BODDY L	Bobby L. Smith Tide	ACCEPTED FOR ALCOHU	
pproved by			IEO 03 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictibious of the United States any false and fictibious of the United States and fictibi