

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 826-9700

4. Location of Well, Footage, Sec., T, R, M  
1610' FSL, 1775' FEL, Sec.13, T-27-N, R-10-W, NMMP

5. Lease Number  
NM-027

6. If Indian, All. or Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
Knauff #2R

9. API Well No.  
30-045-30211

10. Field and Pool  
Fulcher Kutz PC

11. County and State  
San Juan Co, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other -	

## 13. Describe Proposed or Completed Operations

It is intended to change the approved casing and cement program of the subject well. The casing and cement will be altered as follows:

Hole Size	Depth Interval	Csg. Size	Weight	Grade
8 3/4"	0 - 120'	7"	20#	J-55
6 1/4"	0 - 2274'	2 7/8"	6.5#	J-55

Cement

7" surface casing - cement with 46 sx Class "B" cement with 1/4# flocele/sx and 3% calcium chloride (54 cu.ft. of slurry, 200% excess to circulate to surface).

WOC 8 hrs. Test casing to 600 psi for 30 minutes.

2 7/8" production casing - Lead w/221 sx Class "B" w/3% sodium metasilicate, 1/2 pps cellophane and 10 pps gilsonite. Tail w/90 sx 50/50 Class "B" Poz w/2% gel, 1/4 pps cellophane, 5 pps gilsonite and 2% calcium chloride (764 cu.ft. of slurry, 100% excess to circulate to surface). WOC 8 hrs. If cement does not circulate to surface, a CBL will be run during completion to determine TOC.

## 14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 7/31/00  
TLW

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NM000