UNITED STATES

0112222 2111222								
DEPARTM	INE	OF	THE	INTERIOR				
BUREAU	OF	LA	ND M	ANAGEMENT				

	Sundry Notices	and Reports or	Wells	2: 65	
. Type of Well GAS		CTC	HALLES	5. 6.	Lease Number SF-077875 If Indian, All. or Tribe Name Unit Agreement Name
2. Name of Operat	GTQN	S COMPANY	AUG 2000		Well Name & Number
PO Box 4289,	ne No. of Operator Farmington, NM 874	199 (505) 3 6 7	PRECENCIA PRODUCTION DIV) 	Rowley #2R API Well No. 30-045-30212
	ell, Footage, Sec., S'FWL, Sec.8, T-27-N		C. 1919. 1955	in the second	Field and Pool Fulcher Kutz PC County and State San Juan Co, NM
2. CHECK APPROPE	RIATE BOX TO INDICAT	E NATURE OF NO	TICE, REPOR	T, OTHER	DATA
Type of Submis	e of Intent	Type of Abandonment Recompletion		nge of Pla Construct	
Subsec	quent Report	Plugging Back Casing Repair	Non-		Fracturing
T7 4 3					
rinal	AbandonmentX_	_ Altering Cas: _ Other -	ing Conv	ersion to	o Injection
Describe Pr		Other - Operations Operations	and cement	program o	
It is intended well. The	zoposed or Completed ded to change the appearance casing and cement Depth Interval 0 - 120'	Other - Operations oproved casing will be altere Csg. Size 7"	and cement ed as follow Weight 20#	program ovs: <u>Grade</u> J-55	
II is intended well. The	x coposed or Completed ded to change the ap casing and cement Depth Interval	Other - d Operations proved casing will be altere Csg. Size	and cement ed as follow Weight	program ovs:	
It is intended well. The well. The well. The well. The well. The well well well well well well well we	Z Toposed or Completed ded to change the apple casing and cement Depth Interval 0 - 120' 0 - 1925' casing - cement with chloride (54 cu.ft. s. Test casing to 6	Other - Operations Op	and cement ed as follow Weight 20# 6.5# "B" cement wown excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride cs. If cement	program ovs: Grade J-55 J-55 vith 1/4# o circulate sodium me Class "B' (647 cu.ftent does need to the control of the control	flocele/sx and 3% ce to surface). etasilicate, 1/2 pps Poz w/2% gel, 1/4 pc. of slurry, 100% not circulate to
It is intended well. The well. The well. The well. The well. The well well well well well well well we	coposed or Completed ded to change the apple casing and cement Depth Interval 0 - 120' 0 - 1925' casing - cement with the chloride (54 cu.ft.) s. Test casing to expect the and 10 pps gilson the controller of circulate to surface controller of circulate to surface deduction casing - Leader the controller of circulate to surface controller of circulate to surface deduction casing - Leader the circulate to surface circulate to surface deduction casing - Leader the circulate to surface circulate to surface deduction casing - Leader the circulate to surface circulate to surface circulate to surface circulate to surface circulate ci	Other - Operations Oproved casing will be altered Csg. Size 7" 2 7/8" 1 46 sx Class Of slurry, 200 Of w/181 sx Class Oid w/181 sx Class	and cement ed as follow Weight 20# 6.5# "B" cement w 0% excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If ceme	program ovs: Grade J-55 J-55 with 1/4# o circulate sodium me Class "B' (647 cu.ft) ent does remine TOC	flocele/sx and 3% ce to surface). etasilicate, 1/2 pps Poz w/2% gel, 1/4 pc. of slurry, 100% not circulate to
It is intend well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" producellophane excess to surface, I hereby cessigned way (coposed or Completed ded to change the apple casing and cement Depth Interval 0 - 120' 0 - 1925' casing - cement with chloride (54 cu.ft. s. Test casing to detection casing - Leader and 10 pps gilson detection casing correctly that the forement of the control	Other - Operations Oproved casing will be altered Csg. Size 7" 2 7/8" 1 46 sx Class of slurry, 200 0 psi for 30 0 w/181 sx Class oite. Tail w/9 and 2% calcium ace). WOC 8 hiduring complet: Egoing is true Title Requi	and cement ed as follow Weight 20# 6.5# "B" cement w 0% excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If ceme ion to deter	program ovs: Grade J-55 J-55 with 1/4# o circulate sodium me Class "B' (647 cu.ft) ent does note that the control of the con	flocele/sx and 3% te to surface). etasilicate, 1/2 pps Poz w/2% gel, 1/4 pt. of slurry, 100% not circulate to
It is intend well. The well. The well. The Hole Size 8 %" 6 %" Cement 7" surface of calcium of WOC 8 hrs 2 7/8" producellophar excess to surface, It hereby center for Figure 1 for Figure 1 for Figure 1 for Figure 2 for Figure 2 for Figure 2 for Figure 3 for Figure 2 for Figure 3 for Figur	coposed or Completed ded to change the apple casing and cement Depth Interval 0 - 120' 0 - 1925' casing - cement with the chloride (54 cu.ft.) cas. Test casing to expect the and 10 pps gilson detection casing - Leader the chloride to surface a CBL will be run detection to casing the control of the contr	Other - Operations Oproved casing will be altered Csg. Size 7" 2 7/8" 1 46 sx Class of slurry, 200 0 psi for 30 0 w/181 sx Class oite. Tail w/9 and 2% calcium ace). WOC 8 hiduring complet: Egoing is true Title Requi	and cement ed as follow Weight 20# 6.5# "B" cement w 0% excess to minutes. ss "B" w/3% 90 sx 50/50 m chloride rs. If ceme ion to deter	program ovs: Grade J-55 J-55 with 1/4# o circulate sodium me Class "B' (647 cu.ft) ent does note that the control of the con	flocele/sx and 3% ce to surface). etasilicate, 1/2 pps Poz w/2% gel, 1/4 pc. of slurry, 100% not circulate to