



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.  
Approval expires 12-31-60.

Land Office **Santa Fe**  
Lease No. **077111**  
Unit **Storey**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	<b>XX</b>
NOTICE OF INTENTION TO ABANDON WELL		<b>Water Frac</b>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 12, 19 57

Well No. **10-C (PM)** is located **1090** ft. from **SW** line and **1650** ft. from **W** line of sec. **35**  
**SW Section 35** **28N** **9W** **N.M.P.M.**  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**So. Blanco Ext. & Blanco** **San Juan** **New Mexico**  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6146** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3-4-57. Total Depth 4747. Plug back T.D. 4680.  
 Water fractured Point Lookout perforated intervals 4594'-4611', 4640'-4650'.  
 4656'-4662' with 4 shots per foot with 60,000 gallons water and 60,000# sand.  
 Maximum pressure 1100#, average treating pressure 1100#. Injection rate  
 75.7 bbls./min. Flush 7200 gallons.

3-4-57. Total Depth 4747. Temporary Bridge Plug at 4510.  
 Water fractured Pictured Cliffs perforated intervals 2290'-2330' with 2 shots  
 per foot with 53,200 gallons water and 40,000# sand. Maximum pressure 1500#,  
 average treating pressure 700#. Injection rate 78 bbls./min. Flush 4830 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**

**Farmington, New Mexico**

By **OR'G'NAL SIGNED E. S. OBERLY**

Title **Petroleum Engineer**



