



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 077111

Unit Storey

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 26, 1957

Well No. 9-C (PM) is located 1700 ft. from S line and 950 ft. from W line of sec. 34

SW Section 34

(1/4 Sec. and Sec. No.)

28N

(Twp.)

9W

(Range)

H.M.F.M.

(Meridian)

So. Blanco Ext. & Blanco

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6830 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

On 3-24-57, Total Depth 5095'.
Ran 121 joints 7-5/8", 26.40#, J-55 casing (5082')
set at 5092'. Two stage cementing tool at 3079'. First stage
100 sacks Regular cement, 100 sacks Pozmix with 4% gel and 1/4%
Floccs per sack. Second stage 100 sacks Regular cement, 100
sacks Pozmix with 4% gel and 1/4% Floccs per sack. Held 1000# 30 minutes.
Top of cement by temperature survey on second stage at 2793'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By ORIGINAL SIGNED F.W. BOYD

Title Petroleum Engineer