FOR (I	eb. 19	951)	
		,	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Pe
Lease No.	omu
Unit	Storey

SUNDRY	NOTICES AN	ID REPORTS ON WELLS	
OTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
TICE OF INTENTION TO CHANGE	l l	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.	
TICE OF INTENTION TO TEST WA	l l	SUBSEQUENT REPORT OF ALTERING CASING	
OTICE OF INTENTION TO RE-DRIL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
OTICE OF INTENTION TO SHOOT	1	SUBSEQUENT REPORT OF ABANDONMENT	
OTICE OF INTENTION TO PULL OR	ALTER CASING	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO ABANDO	N WELL	Water Frec	
(INDIC	CATE ABOVE BY CHECK MARK NA	ATURE OF REPORT, NOTICE, OR OTHER DATA)	
	-	Yey 2	, 19.57
ll No. 9-C(PM) is loca	ated 1700 ft. from	S line and S line of sec.	34
(½ Sec. and Sec. No.)	263 9 (R	tange) (Meridian)	
o. Blanco Ext. & Bl	enco Sep J	Subdivision) (State or Territory)	
ne elevation of the derric			
L-30-57. Total Devit	DETAIL to objective sands; show sizes, ing points, and all oth	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.D. 5320. Water fractured Foint	Lookou
tate names of and expected depths -30-57. Total Dept erforated intervals ith 61.000 gallons	DETAIL to objective sands; show sizes, ing points, and all oth 5400. Plug baci 5230-5238; 5248-	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured Foint 1 5256; 5280-5310 with 2 Bynn-Jets per send. Breekdown pressure 2900;	Lookou r foot maximu
tate names of and expected depths 3-30-57. Total Dept erforated intervals with 61.000 mallons	DETAIL to objective sands; show sizes, ing points, and all oth 5400. Plug baci 5230-5238; 5248-	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.D. 5320. Water fractured rount 1 5256; 5280-5310 with 2 Byne-Jets per	Lookou r foot maximu
-30-57. Total Dept erforated intervals ith 61,000 gallons ressure 2900#, aver lush 7610 gallons.	DETAIL to objective sands; show sizes, ing points, and all oth 5400. Plug back 5230-5238; 5248-yeater and 60,000 age treating press	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.D. 5320. Water fractured Foint 1 5256; 5280-5310 with 2 Byna-Jets per sand. Breakdown pressure 2900f, a same 600f. Injection rate 95 bhis.	Lookou r foot maximi /min.
erforated intervals ith 61,000 gallons ressure 2900, aver lush 7610 gallons.	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248-5248-5230-5238; 5248-5400. Temporar	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.D. 5320. Water fractured Foint 1 5256; 5280-5310 with 2 Byna-Jets per grand. Breakdown pressure 2900f, a sure 600f. Injection rate 95 bhis. y Bridge Flug at 5150'. Water fractured	Lookon r foot maximi /min.
ate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900#, aver lush 7610 gallons. -30-57. Total Bept ictured Cliffs perf	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5236; 5248-yeater and 60,000 ago treating pressorated intervals.	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured Foint 1 5256; 5280-5310 with 2 Byna-Jets per sand. Breakdown pressure 2900; a same 600; Injection rate 95 bbls. y Bridge Flug at 5150'. Water fract 2966-2964; 2977-2959 with 2 Byna-Jets	Lookou r foot maximu /min. tured te
rate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900#, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with \$4,600	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- vater and 60,000 age treating press h 5400. Temporar orated intervals gallous water and	S OF WORK , weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.D. 5320. Water fractured Foint 1 5256; 5280-5310 with 2 Byna-Jets per grand. Breakdown pressure 2900f, a sure 600f. Injection rate 95 bhis. y Bridge Flug at 5150'. Water fractured	Lookou r foot maxima /min. tured ts 75%,
rate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900#, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with \$4,600	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- vater and 60,000 age treating press h 5400. Temporar orated intervals gallous water and	S OF WORK weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured Foint 1 5266; 5280-5310 with 2 Byna-Jets per sand. Breakdown pressure 2900f, a sure 600f. Injection rate 95 bbls. y Bridge Flug at 5150'. Water fraction 2946-2964; 2977-2959 with 2 Dyna-Jets 2946-2964; 2977-2959 with 2 Dyna-Jets 4 40,000f sand. Maximum pressure 9	Lookou r foot maxima /min. tured ts 75%,
rate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900#, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with \$4,600	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- vater and 60,000 age treating press h 5400. Temporar orated intervals gallous water and	S OF WORK weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured Foint 1 5266; 5280-5310 with 2 Byna-Jets per sand. Breakdown pressure 2900f, a sure 600f. Injection rate 95 bbls. y Bridge Flug at 5150'. Water fraction 2946-2964; 2977-2959 with 2 Dyna-Jets 2946-2964; 2977-2959 with 2 Dyna-Jets 4 40,000f sand. Maximum pressure 9	Lookou r foot maxima /min. tured ts 75%,
ate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900#, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with 44,600 verage treating pre-	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- water and 60,000 age treating press h 5400. Temporar forsted intervals gallons water and saure 750#, injections	S OF WORK weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.D. 5320. Water fractured rount is 5266; 5280-5310 with 2 Bynn-Jets per sand. Breakdown pressure 2900f, is sure 600f. Injection rate 95 bhis. y Bridge Flug at 5150'. Water fracture 2946-2964; 2977-2969 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 9 setion rate 74 bhis./min. Flush 630	Lookou r foot maxima /min. tured ts 75%,
ate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons ressure 2900#, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with 44,600 verage treating pre-	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- water and 60,000 age treating press h 5400. Temporar forsted intervals gallons water and saure 750#, injections	S OF WORK weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured Foint 1 5266; 5280-5310 with 2 Byna-Jets per sand. Breakdown pressure 2900f, a sure 600f. Injection rate 95 bbls. y Bridge Flug at 5150'. Water fraction 2946-2964; 2977-2959 with 2 Dyna-Jets 2946-2964; 2977-2959 with 2 Dyna-Jets 4 40,000f sand. Maximum pressure 9	Lookou r foot maxima /min. tured ts 75%,
ate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with 44,600 verage treating pre	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- water and 60,000 age treating press h 5400. Temporar forsted intervals saure 750%, injective ork must receive approval in w	s of Work weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured rount is 5266; 5280-5310 with 2 Bynn-Jets per sand. Breakdown pressure 2900f, is sure 600f. Injection rate 95 bhis. Bridge Flug at 5150'. Water fract 2946-2964; 2977-2909 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 96 bhis. Water fract 2946-2964; 2977-2909 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 97 bhis./min. Flush 630 writing by the Geological Survey before operations may be said.	Lookou r foot maxima /min. tured ts 75%,
ate names of and expected depths -30-57. Total Dept erforated intervals ith 61,000 gallons reasure 2900, aver lush 7610 gallons. -30-57. Total Dept ictured Cliffs perf er foot with 44,600 verage treating pre- I understand that this plan of w	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- water and 60,000 age treating press h 5400. Temporar forsted intervals saure 750%, injective ork must receive approval in w	s of Work weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured rount is 5266; 5280-5310 with 2 Bynn-Jets per sand. Breakdown pressure 2900f, is sure 600f. Injection rate 95 bhis. Bridge Flug at 5150'. Water fract 2946-2964; 2977-2909 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 96 bhis. Water fract 2946-2964; 2977-2909 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 97 bhis./min. Flush 630 writing by the Geological Survey before operations may be said.	Lookou r foot maxima /min. tured ts 75%,
30-57. Total Dept orforated intervals ith 61,000 gallons ressure 2900, aver lush 7610 gallons. 30-57. Total Dept ictured Cliffs perfer foot with 44,600 verage treating pressure treating pressure treating pressure treating pressures.	DETAIL to objective sands; show sizes, ing points, and all oth h 5400. Plug back 5230-5238; 5248- water and 60,000 age treating press h 5400. Temporar forsted intervals saure 750%, injective ork must receive approval in w	s of Work weights, and lengths of proposed casings; indicate mudding jour important proposed work) k T.B. 5320. Water fractured rount is 5266; 5280-5310 with 2 Bynn-Jets per sand. Breakdown pressure 2900f, is sure 600f. Injection rate 95 bhis. Bridge Flug at 5150'. Water fract 2946-2964; 2977-2909 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 96 bhis. Water fract 2946-2964; 2977-2909 with 2 Bynn-Jets d 40,000f sand. Maximum pressure 97 bhis./min. Flush 630 writing by the Geological Survey before operations may be said.	Lookou r foot maxima /min. tured ts 75%,