(1	Feb. 1	951)	

(SUBMIT IN TRIPLICATE)	Land Office Sents Pe
UNITED STATES	Lease No. 078329
RTMENT OF THE INTERIOR	Unit Davis

DEPAR **GEOLOGICAL SURVEY**

	ENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
	ENTION TO CHANGE PLANS	
	ENTION TO TEST WATER SHUT-OFF	The state of the s
	NTION TO RE-DRILL OR REPAIR WELL	The state of the s
•	ENTION TO SHOOT OR ACIDIZE	The state of the s
	ENTION TO PULL OR ALTER CASING	
	ENTION TO ABANDON WELL	The state of the s
	(INDICATE ABOVE BY CHECK M	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
		April 2 , 19 5
ell No.	3 is located 1750 ft. fr	rom ${S \atop S}$ line and 990 ft. from ${W \atop W}$ line of sec. 32
i Section	32 285	98 NamaPana
(% Sec. ar	id Sec. No.) (Twp.)	(Range) (Meridian)
		nty or Subdivision) (State or Territory)
30-57.	Potal Depth 4640'.	an other important proposed work)
30-57. 1 m 11 joi 153' to h	Total Depth 4640'. ste 5-1/2', 15.50#, 3-55 639' with 50 macks regal for 30 minutes.	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) casing (386°) set from arrowant, 50 sacks Founix, 45 gal.
-30-57. (m 11 joi 153' to h	Total Depth 4640'. ute 5-1/2', 15.50#, J-55 639' with 50 macks resul	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) casing (386°) set from arrowant, 50 sacks Founix, 45 gel.
-30-57. : un 11 joi: 153' to 4: 14 1000#	Fotal Depth 4640'. Ite 5-1/2', 15.50#, J-55 639' with 50 macks regul for 30 minutes. But by temperature surve	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) casing (386°) set from arrowant, 50 sacks Posmiz, 45 gel.
m 11 join 153' to he 16 1000 p of com	Fotal Depth 4640'. Ite 5-1/2', 15.50#, J-55 639' with 50 macks regul for 30 minutes. But by temperature surve	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) casing (386') set from ar casent, 50 sacks Posmiz, 45 sel. APR 4 .057 OIL CON. CON
-30-57. (m 11 joi 153' to h 14 1000 p of com	Total Depth 4640'. Ite 5-1/2', 15.50#, J-55 639' with 50 macks regul for 30 minutes. Int by temperature surve	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) casing (386') set from arrowant, 50 sacks Possiz, M sel. APR 4 357 Oil CON. CON
I understand the	Fotal Depth 4640'. Its 5-1/2', 15.50#, J-55 639' with 50 macks regal for 30 minutes. Int by temperature surve It Paso Matural Gas Co	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) casing (386') set from ar casent, 50 sacks Posmiz, 45 sel. APR 4 .057 OIL CON. CON

Budget	Bureau	No.	42-R358.4.
Approv	al expire	× 12-	-31-60.

For (I	m 9-	881 a 851)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Pe
Lease No	078329
Unit	Theresan

Section 32 Sectio			SUBSEQUENT REPORT	OF WATER SHUT-OFF	
Subsequent report of Altering Casing. Subsequent report of Altering Casing. Subsequent report of Repairing or Repairing Subsequent Report of Repairing Repairing Subsequent Report of Repairing Report of Report Report of Report Report of Repairing Report of Repairing Report of Repairing Report of Repairing Report of Report Report of Report Report of Report of Report of Report of Report Report of Report Report of Report Report of Report of Report Report of Report of Report Report of Report of Report of Report of Report Report of Report of Report Report of Report of Report Report Report of Report Report Report Report of Report Report Report Report Report Repor	CE OF INTENTION TO DRILL	OF PLANC	SUBSEQUENT REPORT	OF SHOOTING OR ACIDIZING	
Subsequent report of Re-Drilling or Repair CE OF INTENTION TO RE-ORLL OR REPAIR WELL CE OF INTENTION TO SHOOT OR ACIDIZE CE OF INTENTION TO SHOOT OR ACIDIZE CE OF INTENTION TO SHOOT OR ACIDIZE CE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) NO. 3 is located 1750 ft. from S line and 990 ft. from W line of sec. 32. Section 32 28	CE OF INTENTION TO CHANG	GE PLANS	SUBSEQUENT REPORT	OF ALTERING CASING	
Subsequent report of Abandonment. Subsequent report of Abandonment. Subsequent report of Abandonment. Supplementary well history. Supplementary.	CE OF INTENTION TO TEST	WATER SHUT-OFF	SUBSEQUENT REPORT	OF RE-DRILLING, OR REPAIR	
Supplementary well history. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF REPOR	CE OF INTENTION TO RE-DR	T OD ACIDITE	SUBSEQUENT REPORT	OF ABANDONMENT	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 2 , 19. No. 3 is located 1750 ft. from S line and 299 ft. from W line of sec. 32. Section 32 28	CE OF INTENTION TO SHOOT	OR ACIDIZE			
No. 3 is located 1750 ft. from Siline and 999 ft. from Wiline of sec. 32 Section 32 28	CE OF INTENTION TO PULL	DON WELL	Water Frac		
No3 is located 1750 ft. fromS line andS ft. from line of sec					
No. 3 is located 1750 ft. from S line and 990 ft. from W line of sec. 32 Section 32 288	(IN	DICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTIC	E, OR OTHER DATA)	
Section 32 (West and Sec. No.) (Field) (Field) (County or Subdivision) (State or Territory) (State or Territory) (State or Territory) (Pield) (Pield) (County or Subdivision) (State or Territory) (State or Ter				April 2	, 19.5
Section 32 (West and Bec. No.) (Twp.) (Range) (Range) (Range) (Range) (Renge) (State or Territory)			(M)	West	. 20
Section 32 (We see and Sec. No.) (Twp.) (Range) (Range) (Meridian) (State or Territory) (State or Terri	No. 3 is le	ocated 1750 ft. from	S line and S	ft. from \overline{W} line of	r sec ≥
(% Sec. and Sec. No.) Blanco (Field) (County or Subdivision) (State or Territory) elevation of the derrick floor above sea level is 6100 ft. DETAILS OF WORK names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerring points, and all other important proposed work) 1-1-57. Total Depth 1640'. Plug back T.D. 1561'. 1-1-57. Total Depth 1640'. Plug back T.D. 1561'. 1-1-57. Total Depth 1640'. Plug back T.D. 1561'. 1-1-57. Total Depth 1650-1524' (2 shorts per foot) with 75,000 gallons water and 100,000 sand. Breekeown pressure 1800, maximum treating pressure 1 average treating pressure 900. Injection rate 50.0 bbls./min. Flush 25,000 gallons. El Paso Estural Gas Company Box 997		28	94	.N.F.M.	
elevation of the derrick floor above sea level is 6100 ft. DETAILS OF WORK names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coming points, and all other important proposed work) 1-57. Total Depth 4640'. Plug back T.D. 4561'. Water fractured Point Lookeut perforated intervals 4428'-4445'; 1456'-447 1484'-1464' and 4500-4524' (2 shots per foot) with 75,000 gallons water and 100,000 sand. Breakdown pressure 1800f, maximum treating pressure 1800f, maximum treating pressure 25,000 gallons. Injection rate 50.0 bbls./min. Flush 25,000 gallons. In Paso Satural Gas Company Box 997		(1 WP.)	(Range)	Meridian)	
elevation of the derrick floor above sea level is 61.00 ft. DETAILS OF WORK DETAILS OF WORK Inames of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, caming points, and all other important proposed work) 4-1-57. Total Depth 4640'. Plug back T.D. 4561'. Water fractured Point Loukeut perforated intervals 4428'-445'; 4456'-447' 14484'-4464' and 4500-4524' (2 shots per foot) with 75,000 gallons water and 100,000f sand. Breakform pressure 1800f, maximum treating pressure 1800f, maximum treating pressure 1800f, maximum treating pressure 25,000 gallons. Understand that this plan of work must receive approval in writing by the Geological Survey before operations may be somewall. El Paso Estural Gas Company Box 997	Blanco			(State or Territory)	
DETAILS OF WORK In ames of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerring points, and all other important proposed work) 4-1-57. Total Bepth 4640'. Plug back T.D. 4561'. Water fractured Point Lookeut perforated intervals 4428'-4456'; 4456'-446' 14-14-54' and 4500-4524' (2 shorts per foot) with 75,000 gallons water and 100,000 sand. Breakdown pressure 1800, maximum treating pressure 1 average treating pressure 900. Injection rate 50.0 bbls./min. Flush 25,000 gallons. Understand that this plan of work must receive approval in writing by the Geological Survey before operations may be committed. El Paso Estural Gas Company Box 997	(Field)	(county c			
has high and 4500-4524 (2 shots per foot) with 75,000 gallons water that high and 4500-4524 (2 shots per foot) with 75,000 gallons water and 100,000 sand. Breakdown pressure 1800, maximum treating pressure 1 average treating pressure 900. Injection rate 50.0 bbls./min. Flush 25,000 gallons. Lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commonly mpany El Paso Hatural Gas Company					
Hater fractured Point Lookest perforated intervals 19,000 gallons water that this plan of work must receive approval in writing by the Geological Survey before operations may be company El Page Hatural Gas Company Box 997	1 2 27 But-1	Depth 4640'. Plus	6 back T.D. 456	14.	Lest blog
and 100,000 sand. Breakdown pressure 1800, maximum treating pressure 1 average treating pressure 900. Injection rate 50.0 bbls./min. Flush 25,000 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commonly mpany Box 997	delenia IVell				
average treating pressure 900f. Injection rate 50.0 bbls./min. Flush 25,000 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be somewhat mpany Box 997		l Point Lookout pe			table and
25,000 gallons. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commonly mpany El Paso Estural Gas Company Box 997	Water fractured	i Point Lookout pe i 4500-4524' (2 sh	Liciated mark	teh 75.000 pellon	water
understand that this plan of work must receive approval in writing by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations may be communicated by the Geological Survey before operations and the Geological Survey before operations and the Geological Survey by the Geological Survey before operations and the Geological Survey by the Geologi	Water fractured	4500-4524 (2 80	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high -high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high - high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high -high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high -high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high -high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high -high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high -high and and 100,000 se average treating	nd. Breekdom pr og pressure 900f.	rroreted interv ote per foot) w	ith 75,000 gallons	ressure 1
mpany Box 997	Water fractured high which and and 100,000 se average treatin 25,000 gallons.	nd. Breekdown pr ng pressure 900f.	riorated intervotes per foot) we seem 1800f, m	ith 75,000 gallons arises treating positions.	ressure 1
mpany Box 997	Water fractured high which and and 100,000 se average treatin 25,000 gallons.	of work must receive approval	recreted intervented in the per foot) we seem 1800f, make injection rates in writing by the Goological property of the Goological property in writing by the Goological property of the	ith 75,000 gallons arises treating positions.	ressure 1
dress Original Signed EWELL N. WALS	water fractured high and high high and 100,000 se average treating 25,000 gallons. understand that this plan El. Pago	of work must receive approval	recreted intervented in the per foot) we seem 1800f, make injection rates in writing by the Goological property of the Goological property in writing by the Goological property of the	ith 75,000 gallons arises treating positions.	ressure 1
LILLO DOE NICOLO ENTE ENTE	water fractured high and 100,000 se average treating 25,000 gallons. understand that this plan mpany Il Paso	of work must receive approval	recreted intervented in the per foot) we seem 1800f, make injection rates in writing by the Goological property of the Goological property in writing by the Goological property of the	ith 75,000 gallons arises treating positions.	ressure 1
onginal digital there is integr	water fractured high and 100,000 sa average treating 25,000 gallons. understand that this plan mpany 21 Page 2007	of work must receive approval	recreted intervented in the per foot) we seem 1800f, make injection rates in writing by the Goological property of the Goological property in writing by the Goological property of the	ith 75,000 gallons maining properties. 50.0 bbls./min.	Flush Los committee
T	water fractured thick thick and and 100,000 sa average treatin 25,000 gallons. understand that this plan mpany El Paso dress Box 997	of work must receive approval	in writing by the Geologica	ith 75,000 gallons arises treating positions.	Flush Los committee
Til. Petroleum Engineer	ister fractured high '-thgh' and and 100,000 sa average treatin 25,000 gallons. I understand that this plan empany El Paso idress Box 997	of work must receive approval	in writing by the Geologica	original Signed EWEL	Flush L N. WALSI