

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Undesignated Dakota Formation Dakota County San Juan
Initial X Annual _____ Special _____ Date of Test 9-23-60
Company Dalby-Taylor Oil Corporation Lease Dalby-Turn Well No. 1
Unit SW/4 Sec 36 Twp. 35-N Rge. 6-W Purchaser _____
Casing 5-1/2" Wt. 176 I.D. 4.892 Set at 8748 Perf. 8744-60 To 8126-6498
Tubing 2-3/8" Wt. 4.76 I.D. 1.906 Set at 8648 Perf. Open ended To _____
Gas Pay: From 8498 To 8678 L _____ xG 0.687 -GL _____ Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well Single gas
Single-Bradenhead-G. G. or G.O. Dual _____
Date of Completion: 9-11-60 Packer None Reservoir Temp. _____

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										7 Days
1.		<u>2/8"</u>	<u>428</u>		<u>88°</u>	<u>428</u>	<u>88°</u>	<u>1888</u>		3 Hours
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.365</u>		<u>428</u>	<u>0.9741</u>	<u>0.9592</u>	<u>1.043</u>	<u>3943</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2054 P_c² 421836

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.									
2.									
3.									
4.									
5.									

Absolute Potential: 6283 MCFPD; n 0.73
COMPANY Dalby-Taylor Oil Corporation
ADDRESS P. O. Box 1190, Farmington, New Mexico
AGENT and TITLE J. F. Berry - Dist. Engineer
WITNESSED Bob Mitchell
COMPANY El Paso Natural Gas Company

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressibility factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

STATE OF NEW MEXICO	
OIL CONSERVATION COMMISSION	
AZTEC DISTRICT OFFICE	
NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	✓
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	