

Form 9-331b  
(April 1952)


(SUBMIT IN TRIPLICATE)

Indian Agency \_\_\_\_\_

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee Jennepah

Lease No. 14-20-603-742



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jennepah

Farmington, New Mexico May 28, 1957

Well No. 1 is located 1745 ft. from N line and 1160 ft. from E line of sec. 36

NE 1/4 of Section 36 T-28-N R-9-W NMZN  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

South Blanco-Pictured Cliffs San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is 5827 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On May 14, 1957, this well was perforated with 4 shots per foot 2046-65 and 2 shots per foot 2065-67. These perforations were sand-water fracked with 25,000 gallons water and 35,000 pounds sand. Formation broke at 2300#. Injection rate 39.2 BPM.

Preliminary test 3310 MCFPD.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company PAN AMERICAN PETROLEUM CORPORATION

Address Box 487

Farmington, New Mexico

By W. J. Smith

Title Field Superintendent

