




LOCATE WELL CORRECTLY

Santa Fe
U. S. LAND OFFICE
SERIAL NUMBER NM 0764
LEASE OR PERMIT TO PROSPECT

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company Kingwood Oil Company Address First National Building
Oklahoma City, Oklahoma
Lessor or Tract U.S.-Knauff "B" Field Wilcoast State New Mexico
Well No. 1 Sec. 31 T. 28N R. 10W Meridian N.M.P.M. County San Juan
Location 875 ft. [N] of [M] Line and 1810 ft. [E] of [W] Line of Sec. 31 Elevation 5769
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon
so far as can be determined from all available records.
Signed [Signature] Title Chief Clerk

Date August 11, 1959
The summary on this page is for the condition of the well at above date
Commenced drilling May 30, 1959 Finished drilling June 15, 1959

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 6214 to 6340 (G) No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from None to No. 3, from to
No. 2, from to No. 4, from to

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From	To	
10-3/4	32.75#	8	LoneStar	367'	Baker				Surface
5-1/2	15.5#	8	C.F.&I.	6418'	Turbojet float shoe		6328	6337	Production
							6312	6322	String
							6216	6260	

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
10-3/4	367'	300	Pump & plug		
5-1/2	6418'	265 sz. Pozmix & 3300# of gilsonite.	Pump & plug.		
		70 sz. Pozmix @ DV tool at 1816'.	Pump & plug.		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set
Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
Perf. 4 jets per ft.,		6328-37' and 6312-22', treated with 34,902 gals. 2% gelled acid				
38,366# of sand. Perf. 4 jets per ft.,		6216-60', treated with 63,000 gals. of 2% gelled acid, 50,000# of sand.				

TOOLS USED

Rotary tools were used from 0 feet to 6421 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

DATES

July 14, 1959 Put to producing Shut in. Waiting on connection.

* The production for the first 24 hours was 73 barrels of fluid of which 42% was condensate emulsion; 58% treatment water; and % sediment. Gravity, °Bé. 56.6°

If gas well, cu. ft. per 24 hours 3,700 MCF Gallons gasoline per 1,000 cu. ft. of gas .35

Rock pressure, lbs. per sq. in. 1850# S.I. surface press. Well test. Well is not connected to sales line as of this date.

EMPLOYEES

Drilled by Contractor Driller
Don Johnston Drlg. Co. Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	1810		Sand & shale
1810	2161	1810	Sand & coal
2161	2298	351	Sand
2298	2365	137	Shale
2365	3660	67	Sand & shale
3660	3752	1295	Shale
3752	4115	92	Sand & Shale
4115	4300	363	Shale
4300	6220	185	Sand & shale
6220	6366	192	Sand
6366	6421	146	Shale & sand
		55	Sch. tops: Pictured Cliffs, 1691'
			Chacra, 1628'
			Cliff House, 3232'
			Point Lookout, 4030'
			Gallup, 5253'
			Greenhorn, 6050'
			Dakota, 6134'
			Main Bence of Dakota, 6214'

11/17/2000 10:00 AM

APPENDIX 1

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of drilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

HISTORY OF OIL OR GAS WELL

U.S. GOVERNMENT PRINTING OFFICE

FROM-	TO-	TOTAL FEET	FORMATION
			1. 1000
			2. 1000
			3. 1000
			4. 1000
			5. 1000
			6. 1000
			7. 1000
			8. 1000
			9. 1000
			10. 1000
			11. 1000
			12. 1000
			13. 1000
			14. 1000
			15. 1000
			16. 1000
			17. 1000
			18. 1000
			19. 1000
			20. 1000
			21. 1000
			22. 1000
			23. 1000
			24. 1000
			25. 1000
			26. 1000
			27. 1000
			28. 1000
			29. 1000
			30. 1000
			31. 1000
			32. 1000
			33. 1000
			34. 1000
			35. 1000
			36. 1000
			37. 1000
			38. 1000
			39. 1000
			40. 1000
			41. 1000
			42. 1000
			43. 1000
			44. 1000
			45. 1000
			46. 1000
			47. 1000
			48. 1000
			49. 1000
			50. 1000
			51. 1000
			52. 1000
			53. 1000
			54. 1000
			55. 1000
			56. 1000
			57. 1000
			58. 1000
			59. 1000
			60. 1000
			61. 1000
			62. 1000
			63. 1000
			64. 1000
			65. 1000
			66. 1000
			67. 1000
			68. 1000
			69. 1000
			70. 1000
			71. 1000
			72. 1000
			73. 1000
			74. 1000
			75. 1000
			76. 1000
			77. 1000
			78. 1000
			79. 1000
			80. 1000
			81. 1000
			82. 1000
			83. 1000
			84. 1000
			85. 1000
			86. 1000
			87. 1000
			88. 1000
			89. 1000
			90. 1000
			91. 1000
			92. 1000
			93. 1000
			94. 1000
			95. 1000
			96. 1000
			97. 1000
			98. 1000
			99. 1000
			100. 1000