

STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
DISTRICT NO. 3
Phone 99 P. O. Box 697
AZTEC, NEW MEXICO

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 7733
Unit Santa Fe No. 1-6

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Harrison, New Mexico, August 13, 1951
Well No. 1-1 is located 900 ft. from N line and 1000 ft. from E line of sec. 27
N/4 of section 27 (1/4 Sec. and Sec. No.) 27-28-1 (Twp.) 12 (Range) 12 (Meridian)
Richer-Butte (Field) Richer-Butte (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 5000 ft. (S.L.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On July 18, 1951, at 1145 A.M., 5-1/2" casing was set at 1891' with 75 bags of cement. Rotary rig was moved off location and cable tool rig rigged up for drilling cement plug and pay. Well was drilled to a total depth of 2020' with rotary tools. Cable tool rig moved on to well and well cleaned out to bottom.

Well was plugged back with pea gravel from 2020' to 1975' and was set with 503 quarts of 200 from 1975' to 1901' with 5 feet of pea gravel on top of shot July 30, 1951. Well was cleaned out to bottom. 2" tubing was landed at 1987'. Well shut in for 72 hours. Well measured 917 bbl per day after 3 hour blow down through slicker string with 1 1/2" tube through 2" pipe nipple on August 12, 1951.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil and Gas Company

Address Box 187

Harrison, New Mexico

By [Signature]

Title Geological Survey

