

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Redwolf Production, Inc.

3. Address and Telephone No

P. O. Box 5382 Farmington, NM 87499 (505) 326-4125

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL, 1650' FEL
G Section 27, T28N, R10W

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NMSF 077383

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

J. C. Davidson F No. 1

9. API Well No.

30-045-07184

10. Field and Pool, or Exploratory Area

Fulcher Kutz Pictured Cliffs

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-off
☐ Conversion to Injection
☐ Dispose Water

(Note: report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Redwolf Production, Inc. proposes to plug and abandon the subject well as follows:
With tubing and packer, place cement plug from 1601' to 2008' using 67 sx of Class B cement containing 2% CaCl. Place second plug from 807' to 907' using 17 sx of Class B cement. Place plug from 142' to surface both inside and outside of the 5 1/2" casing using 64 sx of Class B cement containing 2% CaCl. A proposed wellbore diagram is attached.

14. I hereby certify that the foregoing is true and correct

Signed

Bruce C. Delventhal

Title

President

Date

23-Dec-97

(This space for Federal or State office)

Approved by

IS/Duane W. Spencer

Title

Date

JAN - 5 1998

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMCCD

**JC DAVIDSON F #1
(PROPOSED)**

**1650' FNL, 1650' FEL
Sec. 27, T28N, R10W**

9 5/8", 40# CSA 92'
CMT W/ 85 SX CMT

Cement plug from 142' to 0'

Cement plug from 807' to 907'

Cement plug from 1601' to 2008'

5 1/2", 17#
CASING SET AT 1909'
W/ 565 SX CMT

1909'

PICTURED CLIFFS

2008'

