Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

		NMSF077383	
SUNDRY NOTICES AND REPORTS ON WELLS		6. If Indian, Allottee or Tribe Name	
Do not use this form for proposals to drill or t	o deepen or reentry to a different reservoir.		
Use "APPLICATION FOR PE			
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation	
I. Type of Well  Gas			
Well Well Other	J. C. Davidson F No. 1		
2. Name of Operator			
Redwolf Production, Inc.	9. API Well No. 30-045-07184		
3. Address and Telephone No.			
P. O. Box 5382, Farmington, NM 87499 (505) 326-4125		10. Field and Pool, or Exploratory Area  Fulcher Kutz Pictured Cliffs 11. County or Parish, State  San Juan County, New Mexico	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			
1650' FNL & 1650' FEL Section 27, T28N, R10W			
12. CHECK APPROPRIATE BOX(s) TO IN	NDICATE NATURE OF NOTICE, REPORT, OR OTHER I	DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent	X Abandonment	Change of Plans  New Construction	
	Recompletion	New Construction  Non-Routine Fracturing	
X Subsequent Report	Plugging Back Casing Repair	Water Shut-off	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
	Other	Dispose Water	
		(Note: Report results of multiple completions on .Well Completion or Recompletion Report and Log form	
	all pertinent details, and give pertinent dates, including estima		
<ol> <li>Describe Proposed or Completed Operations (Clearly state proposed work. If well is directionally drilled, give subsulverk.)*</li> </ol>	rface locations and measured and true vertical depths for all ma	rkers and zones pertinent to this	
The subject well was plugg	ed and abandoned on 2/2/99 as follows:	A cement retainer	
	(74-34 cf) of Class B cement was pumpe		

The subject well was plugged and abandoned on 2/2/99 as follows: A cement retainer was set at 1592' and 67 sx (74.34 cf) of Class B cement was pumped below the retainer. Six sx (7.08 cf) of Class B cement was left on top of the retainer. A cement plug was set from 1057' to 681' through tubing using 42 sx (49.56 cf) of Class B cement containing 2% CaCl. After tagging the top of this plug, two squeeze holes were shot at 142'. A total of 160 sx (188.8 cf) of class B cement was used to fill the 5 1/2" casing and annulus from 142' to surface. Installed dry hole marker.

I hereby certify that the foregoing is true and correct  Signed Wave L. Wellerthal	Title	Vice-President	Date	2/3/99
(This space for Federal or State office )				ALVIII.
Approved by	Title	Date		
Conditions of approval, if any:			FEB 0 31	833

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.