



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **077106**
Unit **Lacey**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Water Frac	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 14, 1957

Well No. **11-B** is located **890** ft. from **[N]** line and **1180** ft. from **[E]** line of sec. **30**

NE Section 30 (¼ Sec. and Sec. No.) **28N** (Twp.) **9W** (Range) **M.M.P.M.** (Meridian)

Blanco (Field) **San Juan** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **5996** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-9-57. Total Depth 4560'. Plug back T.D. 4507'. Water fractured Point Lookout perforated intervals 4370-4384'; 4406-4428'; 4436-4450' and 4460-4470' (2 shots per foot) with 65,500 gallons water and 70,000# sand. Breakdown pressure 3300#, maximum treating pressure 1200#, average treating pressure 1150#. Injection rate 90.0 bbls./min. Flush 8700 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**

Farmington, New Mexico

By **Original Signed DWELL N. WALSH**

Title **Petroleum Engineer**