



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 077106
Unit Lackey "B"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 8, 1961

Well No. 13 is located 1650 ft. from 10N line and 1650 ft. from EW line of sec. 20

SW Section 20 28-N 9-W N.M.P.M.
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Basin Dakota San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level 5264.01 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was originally drilled by Delhi Taylor Oil Corp. as the Lackey No. 2. El Paso Natural Gas has purchased this well with name changed to the El Paso Natural Gas Lackey "B" No. 13. El Paso Natural Gas will be the operator.

RECEIVED
MAR 14 1961
GEOLOGICAL SURVEY
SANTA FE, N.M.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 990

Farmington, New Mexico

By ORIGINAL SIGNED J.J. TILKSON

Title Petroleum Engineer

7/25/60

F. Loc. 1650/S: 1650W Elev. 5855 GL Spd. 7-10 Comp. 1600 TD 1600 PB 1600

Casing S. 1600 @ 1600 W 1600 Sx. Int. 1600 @ 1600 W 1600 Sx. Pr. 5 1/2 @ 1600 W 200 Sx. T. 1600 @ 1600

Csg. Perf. 36.80-55, 44-50, 6572-76, 156-75, 2522-48 Prod. Stim. 5201 ACP

I.P. 47.55 MCF/D After 3 Hrs. SICP 2552 PSI After 7 Days GOR 1600 Grev. 1600 1st Del. 1600

TOPS		NITD	X	Well Log		TEST				DATA			
Kirtland		C-102		Plot	X	Schd.	PC	Q	PW	PD	D	Ref. No.	
Fruitland		C-103	✓✓	Electric Log	✓✓✓								
Pictured Cliffs		C-104		C-110									
Cliff House				✓-1.2.2	✓								
Menefee		Ditr		Dfa									
Point Lookout		Datr		Dac									
Mancos		Remarks											
Gallup													
Dakota													
Morrison													
Entrada													

W-320

P
o

Jan. | Feb. | Mar. | Apr. | May | June | July | Aug. | Sept. | Oct. | Nov. | Dec.]