Form	9-331 g
(Feb	. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	nev mexico
Lease No.	04500
Unit	McCulley

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	TELL RISTORY
(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA
	Hey 2
	, 19
SW Section 24 2W W	S line and 1020 ft. from W line of sec.
Blanco & Utlant	Juan Hew Hexico
(Field)	r Subdivision) (State or Territory)
DETAIL ate names of and expected depths to objective sands; show size 4-6-57. Rotal Depth 2456'. Ren 109 joints 2454 with 100 ancks results comment	LS OF WORK 15, weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 7-5/8°, 26.40, J-55 casing (2442') set a
ate names of and expected depths to objective sands; show size 4-6-57. Total Depth 2456'. Ran 109 joints 245h with 100 sacks regular cement, followed with 50 sacks regular cement, by temperature survey at 985'. Potal Depth 4770'. 4-11-57. Ran 52 236 to 4765 with 300 sacks regular ield 1000% for 30 simutes. Top of Perforated with 4 way jet at 2460 and 4-6-57.	LS OF WORK 15. weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 7-5/8", 26.40, J-55 casing (2442') set a 100 sacks Poznix, 1/4 Flocele & 45 Gel at. Held 1000; 30 minutes. Top of cene Joints 5-1/2", 15.5, J-55 liner from cenent, 25 gel, 1/4; per sacks Flocele.
DETAIL ate names of and expected depths to objective sands; show size 4-6-57. Total Depth 2456'. Ran 109 joints 245h with 100 sacks regular cement, followed with 50 sacks regular cement by temperature survey at 985'. Potal Depth 4770'. 4-11-57. Ran 56 2396 to 4765 with 300 sacks regular ield 1000 for 30 minutes.	LS OF WORK 15, weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 7-5/8°, 26.40, J-55 casing (2442') set a 100 secks Formix, 1/4 Flocele & 4% Gel at. Held 1000° 30 minutes. Top of center Joints 5-1/2°, 15.5, J-55 liner from
DETAIL ate names of and expected depths to objective sands; show size 4-6-57. Total Depth 2456'. Ran 109 joints 2454 with 100 sacks regular cement, Collowed with 50 sacks regular cement, Total Depth 4770'. 4-11-57. Ran 56 2396 to 4765 with 300 sacks regular Seld 1000; for 30 sinutes. Top of Cerforated with 4 way jet at 2460 and Cepleze pressure 2000;	LS OF WORK 15. weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 17-5/8°, 26.40, J-55 casing (2442') set a 100 sacks Poznix, 1/4 Flocele & 45 Gel at. Held 1000; 30 minutes. Top of came of came of the first sacks flocele. 10 joints 5-1/2°, 15.5, J-55 liner from coment, 25 gel, 1/4; per sacks flocele. 10 casent by temperature survey at 3960'. 11 squeezed perfs w/200 sack heat cement
DETAIL ate names of and expected depths to objective sands; show size 4-6-57. Total Depth 2456'. Ram 109 joints 2454 with 100 sacks regular cement, Tollowed with 50 sacks regular cement, Total Depth 4770'. 4-11-57. Ram 50 2396 to 4765 with 300 sacks regular Total 1000; for 30 minutes. Top of Perforated with 4 way jet at 2560 and	LS OF WORK 15. weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 17-5/8, 26.40, J-55 casing (2442') set a 100 sacks Formix, 1/4 Flocele & 46 Gel at. Held 1000; 30 minutes. Top of case Joints 5-1/2', 15.5, J-55 liner from centert, 25 gel, 1/4; per sacks Flocele. Centert by temperature survey at 3960'. Ind squeezed perfs w/200 sack heat centert.
DETAIL ate names of and expected depths to objective sands; show size 4-6-57. Rotal Depth 2456'. Ran 109 joints 245h with 100 sacks regular cement, collowed with 50 sacks regular cement, collowed with 4770'. 4-11-57. Ran 50 collowed with 4770'. 4-11-57. Ran 50 collowed with 4770' and 50 collowed with 5	LS OF WORK 15. weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 17-5/8, 26.40, J-55 casing (2442') set a 100 sacks Formix, 1/4 Flocele & 46 Gel at. Held 1000; 30 minutes. Top of case Joints 5-1/2', 15.5, J-55 liner from centert, 25 gel, 1/4; per sacks Flocele. Centert by temperature survey at 3960'. Ind squeezed perfs w/200 sack heat centert.
DETAIL Ate names of and expected depths to objective sands; show size 4-6-57. Rotal Depth 2456'. Ran 109 joints 2454 with 100 sacks regular cement, collowed with 50 sacks regular cement, collowed with	LS OF WORK 15. weights, and lengths of proposed casings; indicate mudding jobs, center important proposed work) 17-5/8, 26.40, J-55 casing (2442') set a 100 sacks Formix, 1/4 Flocele & 46 Gel at. Held 1000; 30 minutes. Top of case Joints 5-1/2', 15.5, J-55 liner from centert, 25 gel, 1/4; per sacks Flocele. Centert by temperature survey at 3960'. Ind squeezed perfs w/200 sack heat centert.