

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR RECEIVED
BUREAU OF LAND MANAGEMENT MAIL ROOM

Sundry Notices and Reports on Wells

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1550' FSL, 1850' FEL, Sec. 22, T-28-N, R-10-W, NMPM

5. Lease Number
SF-077383A
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Kutz Deep Test A #1
9. API Well No.
30-045-07296
10. Field and Pool
Fulcher Kutz Pict. Cliffs
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☒ Other - Stimulate
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to run and cement 3 1/2" casing, perforate and fracture stimulate the subject well according to the attached procedure and wellbore diagram.

RECEIVED
SEP 18 1995
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] (LJB2) Title Regulatory Administrator Date 9/7/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:


APPROVED

INMOCD

SEP 11 1995
DISTRICT MANAGER


KUTZ DEEP TEST A #1 PC

UNIT J SECTION 22 T28N R10W
SAN JUAN COUNTY, NEW MEXICO



KUTZ DEEP TEST A #1 PC

UNIT J SECTION 22 T28N R10W
SAN JUAN COUNTY, NEW MEXICO



Pertinent Data Sheet - KUTZ DEEP TEST A #1 PC

Location: 1550' FSL & 1850' FEL, Unit J, Section 22, T28N, R10W, San Juan County, New Mexico

Field: Fulcher-Kutz PC

Elevation: 6058' GL
5' KB

TD: 2206'
PBTD: 2206'

Completed: 4/30/54

Spud Date: 4/16/54

DP #: 50977A
Lease: Fed: SF 077383A
GWI: 100%
NRI: 65.625%
Prop#: 072010700

Initial Potential: Initial Potential = 394 MCF/D, SICP=402 psi

Casing Record:

<u>Hole Size</u>	<u>Csq Size</u>	<u>Wt. & Grade</u>	<u>Depth Set</u>	<u>Cement</u>	<u>Cement (Top)</u>
e12-1/4"	9-5/8"	36# J-55	99'	125 sx.	Circ Cmt
e7-7/8"	5-1/2"	15.5# J-55	2129'	150 sx.	1363' @ 75% Eff.

Tubing Record:

<u>Tbg. Size</u>	<u>Wt. & Grade</u>	<u>Depth Set</u>
1"	1.68#	2142'

Formation Tops:

Ojo Alamo:	1066'
Kirtland Shale:	1210'
Fruitland:	1853
Pictured Cliffs:	2123'

Logging Record: Induction

Stimulation: SOH w/138 qts SNG..

Workover History: NONE

Production history: PC 1st delivered 1954. Current PC capacity is 0 MCF/D. PC cum is 221 MMCF..

Pipeline: SUG

KUTZ DEEP TEST A #1 PC
Workover Procedure
J 22 28 10
San Juan County, N.M.
Lat-Long: 36.644638 - 107.879791

1. Comply to all NMOCD, BLM, & MOI rules & regulations. MOL and RU completion rig. NU 6" 900 series BOP w/flow tee and stripping head. NU blooie line & 2-7/8" relief line.
2. TOH w/1" tbg & lay down. TIH w/4-3/4" bit on 2-3/8" work string & C.O. w/air/mist to new TD 2250'. Load hole w/1% KCL water. TOH.
3. MI Blue Jet. Run an advanced integrated data processing GSL neutron log 2250'-1800'.
4. Run 3-1/2"-OD 9.2# J-55 NUE tbg to TD 2250' w/Omega type latching collar above 2' tbg sub w/notched collar on bottom. Cement w/250sx 50-50 Cl"B" POZ w/2% gel & 6-1/2#sx kolite & 10% salt & 2% Cacl. (yield=1.44 cf/sx). After cmt, break & wash lines, run 2 wiper balls & Omega wiper latching plug, followed by 100 gal 7-1/2% HCL acid. Displace acid w/1%KCL water. Space out using tbg subs & install 3-1/2" csg in new csg spool. Install 6000 psi rental frac valve on 3-1/2" csg.
5. Pressure test csg to 6000 psi. MI Basin Perforating. Run GR-CCL & coorelate to neutron log. Perf PC w/about 14 holes over 100' of PC interval as per Production Engineering Dept. Perf w/2-1/8" SHOGUN SDP STP-2125-401NT 14 gr charges which make a 0.27" hole & 21.8" of penetration in concrete
6. Break down PC perfs down 3-1/2" csg w/2000 gal 15% GCL & 150% excess perf balls. Acidize @ 7 BPM w/max pressure = 6000 psi. Run junk basket to retrieve balls.
7. Spot & fill 2-400 bbl. frac tanks w/2% KCL water. Filter all water to 25 microns. One tank is for gel & one tank is for breakdown water. Usable gel water required for frac is 355 bbls.
8. Frac PC down 3-1/2" csg w/49,000 gals. of 70 quality foam using 30# gel as the base fluid & 80,000# 20/40 Arizona sand. Pump at 55 BPM. Monitor bottomhole & surface treating pressures, rate, foam quality, & sand concentration with computer van. Sand to be tagged w/ 0.4 mCi/1000# Ir-192 tracer. Max. pressure is 6000 psi & estimated treating pressure is 5500 psi. Treat per the following schedule:

<u>Stage</u>	<u>Foam Vol. (Gals.)</u>	<u>Gel Vol. (Gals.)</u>	<u>Sand Vol. (lbs.)</u>
Pad	14,000	4,200	—
1.0 ppg	10,000	3,000	10,000
2.0 ppg	10,000	3,000	20,000
3.0 ppg	10,000	3,000	30,000
4.0 ppg	5,000	1,500	20,000
Flush	(774)	(232)	0
Totals	49,000	14,700	80,000#

Shut well in after frac for six hours in an attempt to allow the gel to break. Treat frac fluid w/the following additives per 1000 gallons:

- | | |
|----------------------|--|
| * 30# J-48 | (Guar Gel mix in full tank - 16,000 gal) |
| * 1.0 gal. Aqua Flow | (Non-ionic Surfactant mix in full tank) |
| * 1.0# GVW-3 | (Enzyme Breaker mix on fly) |
| * 1.0# B - 5 | (Breaker mix on fly) |

KUTZ DEEP TEST A #1 PC - CEMENT 3-1/2" CSG, PERF PC, & FRAC

- * 3.0 gal Fracfoam I (Foamer mix on fly)
- * 0.38# FracCide 20 (Bacteriacide mix on full tank)

9. Open well through choke manifold & monitor flow. Flow @ 20 bbl/hr, or less if sand is observed. Take pitot gauges when possible.
10. Change out frac valve w/tbg head. TIH w/notched collar on 1-1/4" IJ tbg & C.O. to 2248'. Monitor gas & water returns & take pitot gauges when possible.
11. When wellbore is sufficiently clean, TOH & run after frac gamma-ray log from 2248'-1800'.
12. TIH w/1-1/4" IJ tbg w/standard seating nipple one joint off bottom & again cleanout to 2248'. Use expendable check if necessary. When wellbore is sufficiently clean, land tbg @ 2150' KB. Take final water & gas samples & rates.
13. ND BOP & NU wellhead & tree. Rig down & release rig.

Order Wellhead 8/30/15

Approve: *PJB*
Drilling Superintendent

VENDORS:

Logging:	Blue Jet	325-5584
Perfing	Basin	327-5244
Fracturing:	Howco	325-3575
RA Tag:	Pro-Technics	326-7133
Csg Equip:	Howco	325-3575
Cmt	Howco	325-3575

PMP