OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:LACKEY B LS 010 RTU: 0-000-00 County: SAN JUAN Meter #:71827 ITYPE PROD! METHOD PROD ! MEDIUM PROD I NAME RESERVOIR OR POOL FLOW UPR | LACKEY B LS 010 PC 71827 GAS COMP ! GAS : FLOW TBG LWR | LACKEY B LS 010 MV 71826 PRE-FLOW SHUT-IN PRESSURE DATA ! Hour/Date Shut-In ! Length of Time Shut-In ! SI Press. PSIG ! Stabilzed WEIL TAA ON UPR ! 08/03/92 COMP: 1 2:45P 8/22/90 : 08/03/92 LWR COMP ! 2:45 P FLOW TEST DATE NO. 1 ! Zone Producing (Upr/Lwr) Commenced at (hour,date)* 2:459 PRESSURE LAPSED TIME | ! Prod ! Upper ! Lower ! Temp. SINCE* (hour, date) | 08/03/92 Day i Both Zones SI 08/04/92 Day 2 430 Day 3 08/05/92 08/06/92 Dav 4 08/07/92 Dav 5 08/08/92 Dav 398 Production rate during test Dil: 3.9 BOPD based on 8.7 BBLs in 72 Hrs 56 Grav GOR MFCPD: Tested theu (Orifice or Meter): METER MID-TEST SHUT-IN PRESSURE DATA ! Hour,Date SI : Length of Time SI : SI Press. PSIG : Stabilized (yes/no) 2:45 1 日中央 COMP 2: 45 P (Continue on reverse side)

FLOW TEST NO. 2

Zone producing (Upper or Lower):

TIME frow, date)	LAPSED TIME SINCE ##	PRESSURE		PROD. ZONE		
		Upper Completion	Lower Completion	TEMP.	REMARKS	
· - 						
÷	100 mm 100 mm 11		1870 877			· · · · · · · · · · · · · · · · · · ·
						_
	-			•		
						
		<u> </u>	<u> </u>	1	(
Production rate d	uring test	n dente de la composition della composition dell	e construire de la cons	en e	* ***	
		 پيهنسد ره مد يوخه د په سخه			Grav	
Oil:	BOP	D based on	Bbls. ir	Hours.	Grav	GOR
Gas:		мс	PD: Tested thru	(Orifice or Meter	·):	
				/	<i>/</i> · —————	
			· · · · · · · · · · · · · · · · · · ·			
			· · · · · · · · · · · · · · · · · · ·		·	
Remarks:						
Remarks:			ned is true and co	omplete to the be	st of my knowledge	7
Remarks:	hat the informat	ion herein contain	ned is true and co	omplete to the be	st of my knowledge	Product
Remarks:	hat the informat	ion herein contair	ned is true and co	omplete to the be	st of my knowledge	roductes
Remarks:	hat the informat	ion herein contair	ned is true and co	omplete to the be	st of my knowledge	Productes As
I hereby certify to Approved New Mexico C	hat the informat	ion herein contair	ned is true and co	Operator	st of my knowledge.	roductes
Remarks: I hereby certify to Approved New Mexico Co	hat the information in the conservation in the	ion herein contair	ned is true and co	Operator By Title	st of my knowledge	roductes

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

ed at thour, date) **

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shart-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Text'No. 2 shall be conducted even though no leak was indicated during Flow Text No. 1. Procedure for Flow Text No. 2 is to be the same as for Flow Text No. 1 except

- that the previously produced zone shall remain shot-in while the zone which was previously shot-in is produced.
- 7. Pressures for gas-zone rests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each rest, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Artec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).