



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 87 077303
Unit J. C. Davidson "G"

SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|---|---|
| NOTICE OF INTENTION TO DRILL..... | SUBSEQUENT REPORT OF WATER SHUT-OFF..... |
| NOTICE OF INTENTION TO CHANGE PLANS..... | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | SUBSEQUENT REPORT OF ALTERING CASING..... |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | SUBSEQUENT REPORT OF ABANDONMENT..... |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | SUPPLEMENTARY WELL HISTORY..... |
| NOTICE OF INTENTION TO ABANDON WELL..... | |

RECEIVED
OCT 30 1959
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

J. C. Davidson "G"

Farmington, New Mexico October 28, 1959

Well No. 1 is located 1870 ft. from [N] line and 790 ft. from [E] line of sec. 21

NE/4 of Section 21
(1/4 Sec. and Sec. No.)

T-28-N
(Twp.)

R-10-W
(Range)

S.N.P.M.
(Meridian)

Angels Peak Delta
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6024 ft. (GL)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 6675' - 4-1/2" casing was set at 6675' with 400 sacks 6% gel cement containing 1-1/2 pounds Tuf-Plug per sack followed by 100 sacks neat cement on first stage. Tested casing with 3000 psi which held with no indication of pressure drop. Cemented second stage with collar at 2931' with 250 sacks 4% gel cement. Tested casing with 3000 psi which held with no indication of pressure drop. Received good returns thruout both stages. Drilled 2-stage tool and cleaned out to plug back depth of 6441'. Circulated hole clean and left tubing and bit in hole. Released rotary rig on October 13, 1959. Moved in completion unit on October 15, 1959 to commence completion operations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487

Farmington, New Mexico

Attn: L. O. Speer, Jr.

ORIGINAL SIGNED BY
R. M. Bauer, Jr.

By

Title Area Engineer



