
Form (Feb.	9 -38 1 1951)	l a.
<u></u>	T	

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. SF=077383
Unit d. C. Davidson HHW



UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
OTICE OF INTENTION TO DRILL	OF CHOOTING OR ACIDITING	
OTICE OF INTENTION TO CHANGE PLANS	OF ALTERNAC CASING	
OTICE OF INTENTION TO TEST WATER SHUT-OFF	DE DOULING OF PEPAIR	
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRIEDING	
OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
OTICE OF INTENTION TO ABANDON WELL		
	NOTICE OF OTHER DATA)	
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
J. C. Davidson "H"	Farmington, New Mexico April 26	, 19. 60
1. C. DEVICEOU	(N) (F.),	
ell No1 is located 1650 ft.	from. [N] line and 790ft. from [E] line of sec	<u>22</u>
/4 NE/4 Section 22 T-28-N (¼ Sec. and Sec. No.) (Twp.)	R-10-W N.M.P.M.	
(1/ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)	
Sa Peak Dakota Sa	New Mexico County or Subdivision) (State or Territory)	
(Field)	odnity of Educational,	
	ea level is 5004. ft. (RDB)	
he elevation of the derrick floor above s	, , , , , , , , , , , , , , , , , , ,	
\mathbf{D}_{i}	ETAILS OF WORK	
Di	ETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding	jobs, cemen
denths to objective sands; s	thow sizes, weights, and lengths of proposed casings; indicate mudding	jobs, cemen
itate names of and expected depths to objective sands; a ing points, a pudded 12-1/4# hole on April 20	thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) 1960 and drilled to 342. 8-5/8# casi	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4* hole on April 20, t 342* with 250 sacks coment cou	thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) 1960 and drilled to 342. 8-5/8" casing the state of the state o	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4* hole on April 20, t 342* with 250 sacks coment cou	thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) 1960 and drilled to 342. 8-5/8" casing the state of the state o	rculate
pudded 12-1/4" hole on April 20, t 342' with 250 macks coment coment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4" hole on April 20, to 342; with 250 sacks coment con	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4" hole on April 20, 342' with 250 sacks coment comment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
oudded 12-1/4" hole on April 20, 342' with 250 sacks coment comment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
oudded 12-1/4" hole on April 20, 342' with 250 sacks coment comment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
oudded 12-1/4" hole on April 20, 342' with 250 sacks coment comment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4" hole on April 20, 342' with 250 sacks coment comment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4" hole on April 20, 342' with 250 sacks coment comment. After waiting on coment, and the held with no indication of	thow sizes, weights, and lengths of proposed casings; indicate mudding all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. Cip tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; a ing points, a pudded 12-1/4" hole on April 20, 342' with 250 sacks cement comment. After waiting on cement, aich held with no indication of and resumed drilling operations.	show sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work), 1960 and drilled to 342. 8-5/8" casintaining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
ate names of and expected depths to objective sands; a ing points, a pudded 12-1/4" hole on April 20, 342' with 250 sacks cement comment. After waiting on cement, such held with no indication of and resumed drilling operations.	show sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work), 1960 and drilled to 342. 8-5/8" casintaining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; a ing points, a pudded 12-1/4" hole on April 20, 342' with 250 sacks cement comment. After waiting on cement, aich held with no indication of and resumed drilling operations.	show sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work), 1960 and drilled to 342. 8-5/8" casintaining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8"	rculate
tate names of and expected depths to objective sands; as ing points, as pudded 12-1/4" hole on April 20, to 342' with 250 sacks cement consent. After waiting on cement, hich held with no indication of and resumed drilling operations.	show sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8" APR 28 1960 APR 28 196	reulate 30 min at 342
I understand that this plan of work must receive applications and supplies the names of and expected depths to objective sands; sing points, a pudded 12-1/4* hole on April 20, 342! with 250 sacks cement consent. After waiting on cement, and held with no indication of and resumed drilling operations.	thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8" APR 28 196	reulate 30 min at 342
I understand that this plan of work must receive applications of a large company Pan American Patroles.	thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) , 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8" pressure drop. Reduced hole to 7-7/8" Opposed to the control of t	reulate 30 min at 342
I understand that this plan of work must receive applications of the company — Pan American Patroles.	thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8" APR 28 196 AP	reulate 30 min at 342
tate names of and expected depths to objective sands; a ing points, a pudded 12-1/4" hole on April 20, 342' with 250 sacks cement comment. After waiting on cement, aich held with no indication of and resumed drilling operations.	whow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) 1960 and drilled to 342. 8-5/8" casing maining 2 percent calcium chloride. City tested 8-5/8" casing with 400 psi for pressure drop. Reduced hole to 7-7/8" Proposed in writing by the Geological Survey before operations of the Corporation of th	reulate 30 min at 342