

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP-079634

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McClanahan

9. WELL NO.

#17

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 24-28N-10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Aztec Oil and Gas Company

3. ADDRESS OF OPERATOR

Drawer 570, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

860 FNL & 840 FEL, Section 24-28N-10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, OM, etc.)

5856 Gr

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETS

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL


ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-20-69 Pulled tubing. Ran corrosion log. Set bridge plug at 6000'.
11-21-69 Plug blew up hole from 6000' to 380'. Prepared to kill well.
11-22-69 Drlg out bridge plug at 380'. Clean out to bottom. Pull out hole. Ran corrosion log. Set bridge plug at 6215'. Ran inspection log.
11-23-69 Ran packer. Found hole at 4030'. Set packer at 3753' cmt. w/100# class "C" w/12 1/2# gilsonite, 100 sx class "C", 2% calo. Squeezed w/2500#.
11-24-69 Clean out cmt 3800-3950.
11-25-69 Drlg plug at 6215'. Clean out to TD. Pulled tubing. Ran production strain 200 jts landed at 6356.95. Rig down.



RECEIVED

NOV 28 1969

S. GEOLOGICAL

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE District Superintendent

DATE November 26, 1969

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

