

10-17-0

30-DYE

F. Loc. 290/S; 320/E Elev. 5517 GL Spd. 10-14-60 Comp. 11-30-60 TD 6235 PB 0147Casing S. 10 3/4 615 W Sx. Int. 7 5/8 @ 1645 W 475 Sx. Pr. 4 1/2 @ 6224 W 230 Sx. T. 2 3/8 @ 6116
Csg. Perf. 3545-6135 Prod. Stim. SWFG507 AOF
I.P. 4900 MCF/D After 3 Hrs. SICP 2048 PSI After 7 Days GOR Grav. 1st Del. 5-15-61 \$ 670

TOPS		NITD	Well Log	TEST DATA							Ref. No.
Kirtland		C-103 XXXX	Plot X	Schd.	PC	Q	PW	PD	D		
Fruitland		C-104 X	Electric Log XXXXX	8/27/73	738	844	319	369	744		
Pictured Cliffs			C-122 X	7/8/75	541	650	272	270	653		
Cliff House	3054	Ditr	Dfa	5/26/77	567	39	242	284	37		
Menefee	3152	Datr	Dac	4/30/79	648	61	232	324	54		
Point Lookout	3057	C-136 5/29/92		4/21/83	499	7	168	249	6		
Mancos	4185			2/13/85	472	9	204	189	9		
Gallup	5070			4-2-88	463	10	123	185	9		
Sanostee	5485										
Greenhorn	5854										
Dakota 84	6024	/Ohio Oil Co. /Ohio Gov't. #2-15 S 320									
Morrison	6200										
Entrada											
GH Dat	-386										

P
O

Basin Oak, Co. SJ s 15 T 20N R 11W U P Oper. THORNTON OIL CO. Ohio Govt. No. 2