Hour, date shut-in

Lower Completion Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

OPERATOR	SRC
LOCATION	

MELL NO 012E

PERATOR SRC OCATION		EASE CAIN COM	•	ELL NO. 012E			
f WELL: UNIT.	O SECTION 16 NAME OF RESERVOIR OR F	POOL TYPE	OF PROD OF Gas)	METHOD OF PROD. (Flow or Art. Lif		PROD. MEDIUM [bg. or Csg.)	
Upper Completion			5	Flow		TBF	
Lower Completion Dakota							
		PRE-FLOW		F/OW RESSURE DA	,	B 4=	
	our, date shut-in	Lenght of tim		I press. psig		ed? (Yes or No)	
Upper Completion	6.3-9/ Our, date shut-in	3 Da	45	745 I press, psig	<u> </u>	ed? (Yes or No)	
Lower	6-3-9/		fe shut-in S		Stabiliza		
			LOW TEST		1/00		
ommenced at (hour, date)* 6/6/			Zone producing (Upper	or Lower):	04444	
TIME (hour, date)	TIME LAPSED TIME		ESSURE Lower Completi	PROD. ZONE	REMARKS		
6-4-91	1 Day	745-	379		Both Zo	nes s.I	
6-5-91		745	401		Both Zo	Nes S.T.	
6-6-91	3 Day	745-	426		Both Za	NES S.I.	
6-7-91	1 Day	745	357		Lower 7	PONE Flowing	
6-8-9	1 2 Day	745	293		I	ONE Flour	
ODUCTION RATE							
IL:BOPD BASED ONBBLS. INHOURS				GOR			
r:		MCFPD:	TESTED THRU (Ori	face or Meter):			
				SURE DATA			
Upper Completion	ur, date shut-in	Lenght of time	e shut-in SI	press. psig	Stabilize	d? (Yes or No)	

(Continue on reverse side)

SI press. psig

Lenght of time shut-in

JUN1 2 1991

Stabilized? (Yes or No)

OIL CON. DIV.

FLOW TEST NO. 2

TIME	LAPSED TIME	PRESSURE Upper Completion Lower Completion		PROD. ZONE	9534A BWB
(hour, date)	SINCE **			TEMP.	REMARKS
		 			
	i				
•				(Orifice or Meter):	
					
	y that the informat	1991		mplete to the best of	
proved	JUN 13	1991		=	
proved	y that the informate of the conservation	1991		=	
oproved New Mexico	JUN 13	1991 Division	19 C	Operator Sources y Barbara itie Produ	Home Royaltyne Home
pproved New Mexico	Oil Conservation	1991 Division ARLES GHOLSON	19 C	=	Home Royaltyne Home

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven dava arter actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shur-in for pressure stabilization. Both zones shall remain shur-in until the well-head pressure in each has stabilized, provided however, that they need not remain shur-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shur-in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first nour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).