

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Formation County
Initial Special Date of Test 5/19/59
Company Lease Well No. 9
Unit Sec. 11 Twp. 24 Rge. 10 Purchaser
Casing 1.5 Wt. I.D. 1.375 Set at 1951 Perf. 1934 To 1100
Tubing 1 Wt. 1.7 I.D. 1.315 Set at 1951 Perf. 1933 To 1243
Gas Pay: From 1.35 To 1920 L xG -GL Bar.Press.
Producing Thru: Casing XXXX Tubing Type Well Single-Gas
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 5/12/59 Packer Reservoir Temp.

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter)Type Taps

No.	Flow Data			Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	
SI								
1.						595	60	7 days
2.		750				333	72	3 hours
3.								
4.								
5.								

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wPF}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.340		315	.9887	.9408	1.033	1137
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio cc/bbl.
Gravity of Liquid Hydrocarbons deg.
F_c (1-e^{-s})

Specific Gravity Separator Gas
Specific Gravity Flowing Fluid
P_c 607 P_c² 368,449

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.	3					1.1,006	21,149		
2.									
3.									
4.									
5.									

Absolute Potential: 1.0 MCFPD; n .35
COMPANY
ADDRESS
AGENT and TITLE ORIGINAL SIGNED BY D. K. BRYANT
WITNESSED
COMPANY

REMARKS 

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_C = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_{w-} = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

 F_{pv} - Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. 1000	1000	
State	State	
U. S. G. S.	U. S. G. S.	
Transporter	Transporter	
File	File	✓