MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Undesignated FruitlandFormation Fruitland County San Juan											
Initial XX Annual Special Date of Test 3-21-63											
Company Southern Union Prod. Co. Lease Angel Peak Well No. 17											
Unit C Sec. 13 Twp. 28W Rge. 11W Purchaser Southern Union Gas Company											
Casing 5 Wt.14.0 I.D.5.012 Set at 1681 Perf. 1648 To 1688											
Tubing 1 Wt.2.90 I.D.1.610 Set at 1650 Perf. 1640 To 1650											
Gas Pay: From 1648 To 1688 L 1640 xG 640 -GL 1050 Bar. Press.12.0											
Producing Thru: Casing Tubing XX Type Well Single Gas											
Single-Bradenhead-G. G. or G.O. Dual Date of Completion: 3-14-63 Packer 1763 Reservoir Temp.											
Bridge Plug OBSERVED DATA											
Tested Through (Prever) (Choke) (Meter) Type Taps											
Flow Data Tubing Data Casing Data										1	
(Prover) No. (Line)		(Choke) Pre	ss. Diff.		Press.	Temp.	Press.	Тежр.	Duration of Flow	
	Size	Size	ps	ig h _w	°F.	psig	°F.	psig	°F.	Hr.	
SI 1.	211	3/1	h 93	7	58	629 217	58	629 481	· · · · · · · · · · · · · · · · · · ·	7 day 3 hrs	
2.					70						
3.		<u> </u>					<u> </u>				
4. 5.											
FLOW CALCULATIONS											
	Coefficient		 .		Flow	low Temp. Gr					
No.	(24-Hour)		$\sqrt{h_{\mathbf{W}}p_{\mathbf{f}}}$ psia		Factor F+		Factor F _a	Factor	r	Q-MCYPD ● 15.025 psia	
1.			229		1.0019		.9682 1.021		1 2804		
1. 2.											
3° 4° 5°											
5.											
PRESSURE CALCULATIONS Gas Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas Specific Gravity Flowing Fluid Pc (1-e-8) Pc 641 Pc 410.9											
No.	$P_{\mathbf{W}}$	Pt ²	F _c Q	$(F_cQ)^2$	· (F	c ^Q) ²	P _w 2	P _c ² -P _w ²	Ca	al. P.	
ŀ	Pt (psia)	- t	- c -	(-64)	(i	€ 0)			1	Pw Pc -769	
1. 2.							243.0	167.9		-759	
3.									ļ. <u>.</u>		
4. 5.									+		
Absolute Potential: 6,000 MCFPD; n85											
	PANY RESS			Union Pr							
	NT and TITLE	Ver	ne Roc	khold.	unior	nginee	r				
WITNESSED Wayne B. Smith											
COMPANY New Mexico Oil Conservation Commission REMARKS											
(1) Mr. Paul Clote											
	(1) Mr. L. S. Muennink MAR 2 / 1963										
	(1) Mr. Val A. Ripper										
(1) Mr. Bob Corliss (1) Mr. Rudy Motto (1) File											

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- FgI Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_W cannot be taken because of manner of completion or condition of well, then P_W must be calculated by adding the pressure drop due to friction within the flow string to P_+ .