

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO.
2. NAME OF OPERATOR	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	8. FARM OR LEASE NAME
14. PERMIT NO.	9. WELL NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	10. FIELD AND POOL, OR WILDCAT
	11. SEC., T., R., N., OR BLE. AND SURVEY OR AREA
	12. COUNTY OR PARISH
	13. STATE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data



NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	REPAIRING WELL	☐
SHOOT OR ACIDIZE	☐	ALTERING CASING	☐
REPAIR WELL	☐	ABANDONMENT*	☐
(Other)	☒ Re-work well	(Other)	☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to re-work well as follows:

1. Pull tubing. Clean out to total depth of 1885 feet.
2. Run casing inspection log in 5-1/2" casing and determine condition of casing.
3. If casing is corroded a full string of 3-1/2", 9.20#, J-55 tubing will be run and set at T.D. of 1885 feet and cemented to surface. If casing is good a 4" O.D., 11.67#, J-55 flush joint liner will be run from T.D. 1885 to 1690 feet and cemented.
4. Pictured Cliffs zone will be perforated and fraced.
5. 1-1/2" tubing will be run and set at approximately 1820 feet.



18. I hereby certify that the foregoing is true and correct

SIGNED <u>Gilbert D. Noland, Jr.</u>	TITLE <u>Drilling Superintendent</u>	DATE <u>July 31, 1964</u>
(This space for Federal or State office use)		
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.