NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Bo	sin			_Formatio	n D	akota		County_	San .	Juan	
Initi	al X		Annu	al		Sp e	cial		Date of	Test_	7-31-61	
Company Redfern & Herd, Inc.							370	We	ll No	5		
	N											
	g 4-1/2										6138	
	g 2-3/8											
											ess	
Doto	of Commission	. 00		/2		noving-	Sir	ngle-Brade	enhead-G.	G. or	G.O. Dual	
Jace	of Comple	cion:	0-20	-01	Раске			Reserve	oir Temp.			
						OBSERV	VED DATA					
[este	d Through	(Dist	DARK (Choke) (MODERAL	Ž.			Type Tar	os		
	Flow Data			ata	Tubing Da							
lo.	(Prover) (Line)	(Ci	noke) .fice)	Pres	s. Diff.	Temp.	Press.	Temp.	Press.	Temp.		
	Size		Size	psi	g h _w	o _F .	psig	o _F .	psig	o _F .	of Flo	
I							1785		1715			
	2"	1 3	/4"	31/		820			90/	}	2 3	
			-			02	 	 	994	 	3 hre.	
						L	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	
			+				CULATION					
io .	Coeffici	.ent			Pressure				Compre		Rate of Flow	
(24-Hou		ır)	r) $\sqrt{h_{\mathbf{w}}p}$		psia				Factor		Q-MCFPD 8 15.025 psia	
			V	1	F		-	<u>`g</u>	- pv		6 1)*0c) pste	
۰	12.3650				326	-9795		.9258	1.034		3780	
•			 									
<u></u>					L		<u> L</u>				······································	
					PR	essure c	alcut ati	ONS				
s Lio	uid Hydro	carbo	n Ratio)		cf/bbl.		Sneci	fic Gravi	tv Sens	rator Cae	
avity	of Liqui	d Hyd:	rocarbo	ns	deg. Spe				cific Gravity Separator Gascific Gravity Flowing Fluid			
			(1	-е ⁻⁸])			P _c	797	_P ²	3229	
	W		,		, ,2	1	. 2		2 2			
0• p	t (psia)	P	t Fc	Q	$(F_cQ)^2$	(F	cQ) ² -e-s)	$P_{\mathbf{w}}^2$	$P_c^2 - P_w^2$	Ca	P _w P _c	
	1006				<u> </u>		-6 -)	1012	2217		P _C	
											1.4797	
•												
<u>.</u>										 		
	te Potent	ial·	50:	2	 	MCFPD;	n 15	7 226		<u> </u>	- - 	
OMPAN	Y	edfor	n & He	d. I	pe.			1.326				
DDRES	S 1	007	. Dust	n, F	ermington	. New Me	ori ee					
GENI ITNES	and TITLE SED	OII	dingi si	mea .	by I. A. L	ugan P	ngineer			PEN	[n]	
OMPAN									/Q1	177	FR /	
						REM	ARKS		7	-011	1961	
									\ S	EP11	COM	
									/ 01	L CON	3	
									/	DIST		

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- P_{w} Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{W}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

	بالمواقعة المستعدي
STATE OF NEW MEXICO	!
- SU COUS EVATION COMMISSIO.	
AZE C DISTRICT DIFFICE	
WHEN OF COPPS RECEIVED	3
D ST. 15. 17.3	·· -75.
SANTA FE	
FILE	
U.S.S.S.	
TRANSPORTER GAS	
PROCATION UTILE	
PROMATION OFFICE	