

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

BURLINGTON
RESOURCES

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FSL, 990' FWL, Sec. 12, T-28-N, R-11-W, NMPM

M

Lease Number

SF-047017A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Angel Peak #18

9. API Well No.

30-045-07556

10. Field and Pool

Fulcher Kutz Pict. Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

12-17-96 MIRU. SDON.
12-18-97 ND WH. NU BOP. TOOHH w/60 jts 1 1/4" tbg. TIH w/3 1/2" gauge ring to 1850'. TOOHH. TIH w/3 1/2" CIBP, set @ 1845'. TOOHH. TIH to 1830'. Load hole w/12 bbl wtr. PT csg to 500 psi, failed. Plug #1: pump 18 sx Class "B" neat cmt above CIBP. Displace to 1385'. TOOHH. SDON.
12-19-96 TIH, tag TOC @ 1390'. TOOHH. TIH, perf 3 sqz holes @ 173'. TOOHH. Establish circ down 3 1/2" csg & out intermediate valve. Plug #2: pump 28 sx Class "B" neat cmt down csg & out intermediate valve. Circ 0.5 bbl cmt to surface. WOC. Cut off WH. Fill 3 1/2" csg w/10 sx Class "B" neat cmt. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. (J. Ruybalid, BLM on location).
12-20-96 Realized plug was not set over Ojo Alamo formation. (Notified BLM that dry hole marker would be drilled out). MIRU. Chip cmt around dry hole marker. Weld on 3 1/2" csg collar. NU BOP. SD for weekend.
12-23-96 Establish circ. Drill out cmt @ 0-145'. Circ hole clean w/4 bbl wtr. SDON.
12-24-96 TIH, tag TOC @ 145'. Establish circ. Drill cmt to 178'. TIH to 249'. Circ csg clean w/5 bbl wtr. TOOHH. TIH to 884'. Plug #3: pump 15 sx Class "B" cmt inside 3 1/2" csg @ 522-884'. TOOHH to 190'. Establish circ. Plug #4: pump 10 sx Class "B" cmt inside 3 1/2" csg. Circ 0.25 bbl cmt to surface. ND BOP. Install dry hole marker w/15 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 12-24-96.

14. I hereby certify that the foregoing is true and correct.

Signed *Regan Bradfield* Title Regulatory Administrator Date 2/5/97

(This space for Federal or State Office use)

APPROVED BY */s/ Duane W. Spencer*

Title

Date FEB 12 1997

CONDITION OF APPROVAL, if any:

NMOC