

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

RECEIVED
ELM

5. Lease Designation and Serial No.
SF-047039B

6. If Indian, Allottee or Tribe Name

7. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

PARKER & PARSLEY DEVELOPMENT COMPANY

3. Address and Telephone No. c/o Walsh Engr. & Prod. Corp. 505 327-4892

204 N. Auburn Farmington, New Mexico 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter O, 1210'FSL, 1350'FEL Sec. 8-T28N-R10W

8. Well Name and No.

Day "J" #3

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/12/92 Plug & Abandoned Well as per Attached.

Approved as to plugging of the well bore.
Liability under this permit retained until
surface restoration is completed.

FOR: PARKER & PARSLEY DEVELOPMENT COMPANY

14. I hereby certify that the foregoing is true and correct

Signed

Paul C. Thompson

Title

Paul C. Thompson, P.E.
Agent

Date

10/16/92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

APPROVED

Date

OCT 23 1992

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

RECEIVED
SLM

OCT 20 PM 1:35

PLEG AND ABANDON

113 F. WILKINSON, N.M.

PARKER & PARSLEY DEVELOPMENT COMPANY

DAY "J" NO. 3

1210'FSL, 1350'FEL, SECTION 8-T28N-R10W

San Juan County, New Mexico

- 10/12/92 Notified BIM 10/9/92. Move on A-Plus Well Service Rig. Blow well down. ND wellhead. NU BOP. Pull 12,000# and tubing came free. TOH with 44 jts. 1-1/2" LJ tubing. (Well has 61 jts. above packer and 2 jts. of tail pipe). Pin end on bottom of tubing looks good. Attempted to screw into fish - unsuccessful. PU 4 - 11/16" overshot on 1-1/2" tbg. and worked over fish. Unable to release packer. Fish fell 30' downhole. Top of fish at 1397'. Packer at 1915'. Called Mark Kelly with BIM at his home at 3:00 PM 10/12/92. Received verbal permission to spot cement on top of fish. Pumped 22 sxs (26 cuft) at 1400'. Good circulation. Left 19 jts. 1-1/2" LJ tbg. and Baker Model AD-1 packer in hole. WOC and SD for night.
- 10/13/92 Loaded hole. Est circ out bradenhead. Tag cement at 1273'. Perf 2 holes at 1012'. Set cement retainer at 960'. Cement with 107 sxs (126 cuft) total. 68 sxs (80 cuft) outside 5-1/2 from 1012' to 780' with 100% excess; 9 sxs (11 cuft) below retainer in 5-1/2" from 1012' to 960' with 50% excess; 30 sxs (35 cuft) above retainer in 5-1/2 from 960' to 780' with 50% excess. 50' above and below Ojo Alamo. Pull tubing to 650' and load hole with 9# mud. TOH laying down. Perf 2 holes at 156'. 1st circ thru bradenhead. Pumped 53 sxs (63 cuft) and circ good cement out bradenhead. ND BOP. Cut off wellhead and install dry hole marker. Mix 5 sxs of cement at stub. Rig down. Job completed 10/13/92.

Parker and Parsley
Day J #3
SE/4 8 28N 10W
Plugged and Abandoned

RECEIVED
BLM

92 OCT 20 PM 1:35

GIS FARMINGTON, N.M.

8-5/8"-24# K-55
set @ 106'
Cmt to surf
with 70 sx

Installed P&A marker
Cement with 5 sx.

9.0 ppg mud

Perfs @ 156'
53 sx (63 cu.ft.)

TOC approx. 780'

Cement retainer
@ 960'
Perfs @ 1012'

107sx (126 cu.ft.)
(68 sx outside 5-1/2",
9 sx below retainer
inside 5-1/2", and
30 sx above retainer)

TOC @ 1030'

TOC @ 1273'

22 sx (26.0 cu.ft.)
1400'

TO fish @ 1400'

5-1/2" 14.0# K-55
set @ 1954'
Cement w/ 100 sx

Model AD-1 pkr
@ 1915'

Open Hole to 1993'

Oct. 16, 1992

PCT