

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Federal Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator El Paso Natural Gas Company	8. Farm or Lease Name Lackey B
3. Address of Operator PO Box 990, Farmington, NM 87401	9. Well No. 12 (P&A)
4. Location of Well UNIT LETTER N, 990 FEET FROM THE South LINE AND 1850 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 28N RANGE 9W NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 6345'GL	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Circulated hole, pumped 50 sk. cement below cement retainer which had been set 150' above Dakota perms. Left 15 sks. cement on top of retainer.

Perforated squeeze holes at 4234' (Mesa Verde), spotted 75 sk. cement plug, squeezed 50 sks. through perforations.

Spotted 20 sk. cement plug inside casing across Pictured Cliffs formation (Pictured Cliffs Formation was covered with cement on primary cement job.)

Perforated squeeze holes at 1645' (Ojo Alamo), spotted 50 sk. cement plug and squeezed 25 sks. through perforations.

Cut off and pulled 1500' of 5 1/2" casing, spotted 50 sk. cement plug over the casing stub.

Spotted 15 sk. cement plug at base of the surface pipe, 260'.
Installed Plug & Abandoned marker with 10 sk. cement surface plug.

(An additional subsequent report will be filed after location has been cleaned and leveled.)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Original Signed F. H. WOOD TITLE Petroleum Engineer DATE March 15, 1972

APPROVED BY Original Signed by A. R. Kendrick TITLE PETROLEUM ENGINEER DIST. NO. 3 DATE MAR 15 1972

CONDITIONS OF APPROVAL, IF ANY: