

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

MERIDIAN OIL

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1490' FNL, 1150' FWL, Sec.13, T-28-N, R-10-W, NMPM

5. Lease Number
SF-0796346. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
McClanahan #5Y9. API Well No.
30-045-2134810. Field and Pool
Aztec Pictured Cliffs11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

Type of Action

☐ Abandonment☐ Recompletion☐ Plugging Back☒ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection

13. Describe Proposed or Completed Operations

REVISED

2-7-96 MIRU. SDON.

2-8-96 ND WH. NU BOP. TOO H w/1 1/2" tbg. TIH w/4 1/2" csg scraper to 1889'. TOO H. SDON.

2-9-96 TIH w/RBP, set @ 1830'. Locate hole in csg @ 217'. TOO H. TIH w/FB pkr, found hole in csg @ 500'. Spot 2 sx sd on RBP. Set pkr. Establish injection into hole in csg. Closed bradenhead valve. TOO H w/pkr. TIH. Pump 325 sx Class "B" cmt w/2% calcium chloride. Displaced w/1.5 bbl wtr. Sqz to 450 psi. WOC. SD for weekend.

2-12-96 ND BOP. CO cmt. NU BOP. TIH, drill cmt @ 70'. Drill past top hole @ 253'. PT to 500 psi, OK. Drill to 311'. Circ hole clean. PT to 500 psi, failed. SDON.

2-13-96 Drill 127' cmt. TOO H. TIH, pump 135 sx Class "B" cmt w/2% calcium chloride. Sqz to 400 psi. WOC. SDON.

2-14-96 TIH, tag cmt. Drill cmt @ 380-410'. PT to 500 psi, failed. TOO H. TIH w/csg scraper to 1500'. TOO H. TIH w/FB pkr, set @ 500'. PT to 500 psi, OK. Located holes @ 224' & 446'. Pump 100 sx Class "B" cmt w/2% calcium chloride. Sqz to 700 psi. WOC. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed Reggie Stradwick Title Regulatory Administrator Date 3/4/96

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

MAR 07 1996

FARMINGTON DISTRICT OFFICE
BY 205

2-15-96 TIH, tag TOC @ 60'. Drill through cmt. TOOH. PT to 500 psi, OK. TIH to 240'.
Spot 3 bbl Class "B" cmt. TOOH to 60', pump 1 bbl cmt. Sqz to 400 psi. WOC.
SDON.

2-16-96 TIH, tag TOC @ 60'. Drill through cmt. PT csg to 500 psi, OK. TOOH. TIH w/csg
scraper to 1500'. TOOH. TIH w/retrieving tool to RBP. Blow well & CO to 2015'.
Latch RBP, TOOH. SD for weekend.

2-19-96 TIH w/1 1/2" J-55 10RD tbg, landed @ 1994'. ND BOP. NU WH. RD. Rig released.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

MERIDIAN OIL

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1490' FNL, 1150' FWL, Sec. 13, T-28-N, R-10-W, NMPM

5. Lease Number

SF-079634

6. If Indian, All. or

Tribe Name

7. Unit Agreement Name

8. Well Name & Number

McClanahan #5Y

9. API Well No.

30-045-21348

10. Field and Pool

Aztec Pictured Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☒ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☐ Other -

13. Describe Proposed or Completed Operations

2-7-96 MIRU. SDON.

2-8-96 ND WH. NU BOP. TOO H w/1 1/2" tbg. TIH w/4 1/2" csg scraper to 1889'. Blow well & CO. TOO H. SDON.

2-9-96 ND BOP. CO cmt. NU BOP. Drill @ 70'. TOO H. Drill past top hole @ 253'. Pressure up to 500 psi. Drill to 311'. Circ hole clean. PT to 500 psi, failed. SD for weekend.

2-12-96 Drill cmt. TOO H. TIH to 60'. Pump 135 sx Class "B" cmt w/2% calcium chloride. Sqz to 400 psi. WOC. SDON.

2-13-96 TIH, drill cmt @ 380-410'. PT to 500 psi, failed. TOO H. TIH w/csg scraper to 1500'. TOO H. TIH w/FB pkr, made multiple tool setting. Found holes @ 446' & 224'. Pump 100 sx Class "B" cmt w/2% calcium chloride. Sqz to 700 psi. WOC. SDON.

2-14-96 TIH, tag TOC @ 60'. Drill cmt. TOO H. PT sqz to 500 psi, OK. Isolate hole in csg @ 224-238'. TOO H. TIH to 240'. Pump 3 bbl Class "B" cmt. TOO H to 60'. Reverse circ. Sqz to 400 psi, WOC. SDON.

2-15-96 TIH w/1 1/2" 2.4# J-55 10RD tbg, landed @ 1994'. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed

Title Regulatory Administrator Date 2/21/96

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any: