

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. 14-20-603-781
2. NAME OF OPERATOR AMOCO PRODUCTION COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Allottee
3. ADDRESS OF OPERATOR 591 Airport Drive Farmington, NM 87401		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 790' FSL x 1610' FSL, Section 36, T-28-N, R-9-W		8. FARM OR LEASE NAME Navajo Allotted Gas Com "B"
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5851' CL, 5864' KB	9. WELL NO. 1A
		10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SU/4 SE/4 Section 36, T-28-N, R-9-W
		12. COUNTY OR PARISH San Juan
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Spud & Set Casing ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 13-3/4" hole 12/10/77. Drilled to 274'. Set 9-5/8" 32.3# casing at 274'. Cemented with 340 sx Class "B", 2% CaCl₂. Circulated 10 sx good cement. Tested to 500 psi for 30 minutes; held OK.

Drilled 8-3/4" hole to 2460'. Set 7" 20# casing at 2460'. Cemented with 200 sx Class "B", 50:50 Poz, 6% gel, 2 lbs. Tuf Plug per sx. This was followed with 80 sx Class "B" 50:50 Poz, 6% gel. Circulated 10 sx good cement. Pressure tested to 1000 psi for 30 minutes; held OK.

Drilled 6-1/4" hole to total depth 4667'. Set 4-1/2" 10.5# casing liner 2274-4660'. Cemented with 200 sx Class "B", 50:50 Poz, 6% gel, 2 lbs. Tuf Plug per sx. This was followed with 80 sx Class "B", 50:50 Poz, 6% gel. Reversed out 10 sx good cement.

18. I hereby certify that the foregoing is true and correct

SIGNED <u><i>E. L. Soper</i></u>	TITLE <u>Area Adm. Supervisor</u>	DATE <u>1/17/78</u>
(This space for Federal or State office use)		
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

JAN 18 1978

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.