

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR  
SUPRON ENERGY CORPORATION

3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 790'/N ; 1800'/E line  
AT TOP PROD. INTERVAL: Same as above.  
AT TOTAL DEPTH: Same as above.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 047017 B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Angel Peak "B"

9. WELL NO.  
28

10. FIELD OR WILDCAT NAME  
Kutz Fruitland Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13, T-28N, R-11W, N.M.P.M.

12. COUNTY OR PARISH  
San Jaun

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5792' R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded 9-7/8" hole at 2:45 p.m. 1-1-80.
2. Drilled 9-7/8" hole to T.D. of 210 ft. R.K.B.
3. Ran 5 joints (201 ft.) of 7-5/8", 26.40#, K-55 casing. Landed at 213 ft. R.K.B.
4. Cemented with 120 sacks of class "B" with 3% CaCl. Plug down at 2:15 a.m. 1-2-80. Cement circulated to surface.
5. Waited on cement 12 hours.
6. Pressure-tested casing to 1000 PSI for 15 minutes. Held OK.

Subsurface Safety Valve: Manu. and Type

Set @

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE 1-3-80

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

JAN 08 '80

FARMINGTON DISTRICT

BY

WIS

