## UNITED STATES DEPARTMENT OF THE INTERIOR

5.	LEASE					
	SF	077106				

6.	IF INDIA	N ALI	OTTEE	OR TRIBI	FNAME

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas other	Lackey B		
well well well other	9. WELL NO.		
2. NAME OF OPERATOR	15E		
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Basin Dakota		
Box 289, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 29, T-28-N, R-9-W		
below.) AT SURFACE: 790'N, 880'W	NMPM		
AT TOP PROD. INTERVAL:	San Juan New Mexico		
AT TOTAL DEPTH:			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
	5890' GL		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3030 011		
TEST WATER SHUT-OFF			
FRACTURE TREAT SHOOT OR ACIDIZE			
REPAIR WELL   RECEN	Report results of multiple completion or zone charge on Form 9–330.) _		
MULTIPLE COMPLETE   APR 1 5 1	1980		
CHANGE ZONES			
ABANDON*  U. S. GEOLOGICAI  (other)			
(other) FARMINGTON,	N. M.		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and		

measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 6682'. Ran 212 joints of 4 1/2", 10.5#, KS production casing 6670' Set at 6682'. Float collar set at 6668'. Stage tools set at 4938-2245'. Cemented 4-6-80: 1st stage w/ 439 cu. ft. cement. Wrong plug was dropped and we were unable to cement second stage. 3rd stage w/762 cu. ft. cement. WOC 18 hours. Top of cement at 975'.

Subsurface Safety Valve: Manu. and Type			Se	
18. I hereby certify that the foregoing is t	rue and correct			/ Stablins & List \
SIGNED A. Shise	TITLE Drilling Clerk	DATE .	April	15 ARB& 7 1980
	(This space for Federal or State office use)	)		YOIL CON. COM.
APPROVED BY	TITLE	DATE	[GOLTI	n for Factorial

\*See Instructions on Reverse Side

**NMOCC** 

