

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P. O. Drawer 570, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1620' FNL & 810' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Casing Report ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
FEB 11 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF-079634
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
McClanahan
9. WELL NO.
#14E
10. FIELD OR WILDCAT NAME
Basin Dakota/Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 23, T28N, R10W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5708' GR

Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

COMPLETED OPERATIONS -

2-07-80 Set 5 1/2", 15.5#, K-55 casing (157 joints - 6463.13') at 6457'. Cemented Stage 1 with 160 sacks of 50/50 Class "B" poz with 6% gel and 1/4# floccel per sack, followed by 50 sacks of Class "B" with 2% CaCl₂. Plug down at 2:00 AM, 2-07-80. Cemented Stage 2 with 180 sacks of 50/50 Class "B" poz with 6% gel, followed by 50 sacks of Class "B" with 2% CaCl₂. Plug down at 5:15 AM, 2-07-80.

2-08-80 Cemented Stage 3 with 700 sacks of Class "B", 50/50 poz with 6% gel. Plug down at 10:15 AM, 2-07-80. Circulated cement to surface.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Prod. Mgr.

DATE

2-08-80


(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:



RECORD

*See Instructions on Reverse Side

FEB 11 '80

WATER

BY M. L. Kuchers