STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator E	BURLINGTON I	RESOURC	ES OIL & GAS CO.		Lease	CAIN COM			Vell	2E
Location of Well:	Unit O	Sect NAME OF	16 Twp. RESERVOIR OR POO	028N OL		010W 'PE OF PROD. (Oil or Gas)		SAN JUAN D OF PROD. or Art. Lift)		D. MEDIUM g. or Csg.)
Upper Completion	CHACRA					Gas	FI	OW		ubing
Lower Completion	DAKOTA					Gas	FI	ow	. 7	ubing
			PRE	-FLOW SHUT-II	N PRESS	URE DATA				
Upper Hour, date shut-in Completion 03/15/2002			Length of time shu		css. psig 382	Stabilized? (Yes or No)				
Lower Completion	03/15/2	2002	144 H	ours		201				
				FLOW TE	ST NO. I					
Commenced	at (hour.date)*		03/19/2002	2		Zone producing	(Upper or Lo	ower) UPP	ER	
TIME	LAPSED	TIME	PRE	ESSURE		PROD. ZONE	(-FF	,		
(hour.date)	SINC		Upper Completion	Lower Comp	oletion	TEMP		REMA	RKS	
03/20/2002	120 H	lours	108	201						
03/21/2002	144 H	lours	108	201			-			
							3357			
							.sis	A.		
						40	. 12.4	~ <i>}</i>		
						API	R 2002	ं रे		
							and the second	<u> </u>		
								es)		
								= 7		
							war			
Production rate	during test					9.00		z*		
Oil	BOPD	based on	Bbls.	in	Hours.		Grav.		GOR	
			MOTER TO A							
Gas:			MCFPD; Tested thru	(Orifice or Mete	r):					
			MID	-TEST SHUT-IN	PRESSU	JRE DATA				
Upper	Hour, date sh	iut-in	Length of time shu			ess. psig		Stabilized? (Yes	or No)	
Completion				: -	3. p.	: hais				
Lower Completion	Hour, date sh	ut-in	Length of time shu	t-in	SI pr	ess. psig		Stabilized? (Yes		
775601 389										
.,0001 309				(Continue on	reverse s	ide)				

FLOW TEST NO. 2

Commenced at (hour, da	ate)**		Zone producing (Upper or Lower):						
TIME	LAPSED TIME	PRESSURE		PROD. ZONE		DELLIB.			
(hour, date)	SINCE **	Upper Completion	Lower Completio	n TEMP.	REMAR	RKS			
			<u> </u>						
Draduation rata du	ring tost								
Production rate dur	ring test								
Oil:	ВС	OPD based on	Bbls. in	Hours	Grav.	GOR			
Gas:		MCFPI	D: Tested thru (C	Orifice or Meter):					
Remarks:									
Lhereby certify tha	t the information he	rein contained is true	and complete to	the best of my knowledge					
i nereby certify tha		em contained is true	and complete to	the best of my knowledg					
Approved		1	9	Operator Burlingto	n Resources				
	il Conservation Divi			01	\mathcal{O} .				
				By Odoro A	logs				
					U				
Ву				Title Operations A	ssociate				
AND THE PARTY OF		The second secon		D					
Title				Date Tuesday, March 26, 2002					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in. in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).