

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 900' FSL X 1845' FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) completion ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF-077383-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Davidson Gas Com "G"

9. WELL NO.  
1E

10. FIELD OR WILDCAT NAME  
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SW/4, SE/4  
Section 21, T28N, R10W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.  
30-045-23991

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6120' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Completion operations commenced on 6-20-80. Total depth of the well is 6807' and plug back depth is 6763'. Perforated intervals 6551' to 6563' and 6617' to 6702' with 2 spf, a total of 194, .38" holes. Landed 2-3/8" tubing at 6708'. Blew the well dry with air and released the rig on 6-22-80.

Flow tested the well until 7-11-80 when completion operations commenced again. Sand water fraced with 126,000 gallons frac fluid and 323,000# 20-40 sand.

Landed 2-3/8" tubing again at 6708'. Swabbed the well and released the rig on 7-16-80.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. HART TITLE Adm. Supvr. DATE 7-28-80

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE [Signature] DATE [Signature]  
CONDITIONS OF APPROVAL, IF ANY:

AUG 1 1980  
Burr Warrick  
for DISTRICT ENGINEER

\*See Instructions on Reverse Side

