

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Pioneer Production Corp.

3. ADDRESS OF OPERATOR

Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1850' FSL - 810' FWL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) CSG ☐

SUBSEQUENT REPORT OF:

RECEIVED

APR 21 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-17-80

Went in hole w/drill pipe. Circulated hole 2 hrs. Laid down drill pipe and drill collars. Rigged up csg crew. Ran 159 jts 4-1/2" OD 11.6# K-55 8R ST&C csg. TE 6430.38' set @ 6425' RKB. DV tool @ 4321'. Preflushed hole w/1000 gals spacer 100. Cemented w/225 sx class "H" self stress w/18% salt w/1/4# cello flake per sx. Total slurry 353 cu ft. Estimated cement top 4875'. Had good circulation and reciprocated csg while cementing. Bumped plug w/1600 psi. Held OK. Opened DV tool w/1600 psi. @ 9:00 p.m. Circulated w/rig mud pumps 3 hrs. Cemented second stage thru Dowell DV tool @ 4321'. Had good circulation. Preflushed w/15 bbls CW-100. Cemented w/540 sx 65-35 w/12% gel w/12-1/4# gilsonite per sx w/1/4# cello flake per sx followed by 200 sx 50-50 poz w/2% gel w/10% salt w/1/4# cello flake per sx. Total slurry 1779 cu ft. Circulated 10-15 bbls cement. Bumped plug w/2500 psi. Held OK. POB 1:00 a.m. Set 4-1/2" slips, cut-off csg. Rig released @ 2:00 a.m. 4-18-80.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan

TITLE Agent

DATE

4-18-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCOI

ACCEPTED FOR RECORD

APR 20 1980

FARMINGTON DISTRICT