

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 810' FSL, 1810' FEL "M"

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☒

☐

☐

☐

☐

☐

☐

5. LEASE

SF-077085

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Omler A

9. WELL NO.

3E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 26, T28N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5811' gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/10/81. Well flowing dry gas. Killed well w/1% KCL water. RIH w/tbg. & clean out to PBTD w/foam. Landed tbg. in BOP @ 6237'. Kicked well around w/N<sub>2</sub>. Left well flowing.

2/11/81. RIH w/tbg. to check PBTD. Had 30' of sand fill. Clean out to PBTD @ 6423' w/foam. Killed Dakota w/1% KCL water and POOH w/tbg. RIH w/7" Model D pkr. w/expendable plug on wireline. Set pkr. @ 3185'. Dump 2 sx sand on pkr. & load hole w/2% KCL water. Pressure test pkr. to 3000 PSI. Held OK, Perf'd Chacra w/4" premium csg. gun @ 2 JSPF as follows: 2948-52', 2970-74', total 8', 16 holes. RIH w/tbg. & fullbore 7" pkr. Left hanging @ 2917'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carley J. Statten TITLE Asst. Div. Adm. Mgr. DATE 2/17/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
MAR 10 1981  
FARMINGTON DISTRICT  
BY [Signature]