STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

` OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting pacter leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator Ta	urus Exp	loration U	SA Lesse_	Za	ehr	4	₩c No.	18 E
cation Well: Unit	Sec	Twp. 028	N Rge	010	W	Cou	ncy <u> </u>	AN Jum
·	NAME OF RESERVOIR OR POOL			TYPE OF PROD. (Oil or Gae)		METHOD OF PROD. (Flow or Art. LH1)		PROD. MEDIUM (Tbg. or Cag.)
Upper mpletion			: GAS		Flow			CAQ.
ner DAKOta			GAS		Flow			Tha
	77180	. PRE-FLO	OW SHUT-IN P	RESSURE				
Hour, date shut-in Length of time shut-in			niin OiU	SI proce. paig		Stabilized? (Yes or No)		•
Hour, date shut-in			(A: 12/50 /0-3-97 Length of time shut-in (-2/15		& 7 3 Si press, pelg		Stabilized? (Yes or No)	
wer // 50 9/29/97			94/2hr 10-3.97		451		んの	
			FLOW TEST	NO. 1			•	
immenced at (hour, date) * 12'15 10-3-97				Zone producing (Up		per or Cower;		
TIME (hour, date)	LAPSED TIME SINCE*	PRES: Upper Completion	SURE Lower Completion		ZONE MP.		REMARKS	
120	5 Mio	3 95	447			152 mc	F	ower zon e Monitest
<u>'25</u>	10	295	432			152 mc F		
136	15	295	406			152 M	cF.	····
: 35	20	295	387		· ·	147		
:40	25	295	355			127		
:45	30	295	344			12.2		
duction rate	during test		•					
l:	BOP	D based on	Bbls. is	n	_ Hours	c	Grav	GOR
s:		MCF	PD; Tested thru	ı (Orifice	or Meter	·):		
	•	MID-TT	est shut-in p	RESSURE	DATA			
1pper	Hour, date shut-in - Length of time shut-in		SI press. pelg			Stabilized? (Yes or No)		
Lower mpletion		Length of time shu	Length of time shut-in		SI press, pelg		Stabilized?	(Yes or No)
				•			EO,	8 1807 D

(Continue on reverse side)

FLOW TEST NO. 2

-

disper or Lewis

PROD. ZOME

Cheur, date)	SINCE **	Upper Completion Lower Completion		TEMP.	REMARKS					
	·									
					:					
		•								
Production rate d	uring test									
Oil:	BOP	D based on	Bbls. in	Hours.	Grav GOR					
Gas:		MCF	PD: Tested thru	(Orifice or Meter)):					
Remarks:			<u>.</u> .							
	· .									
I hereby certify th	nat the information	on herein contain	ed is true and co	mplete to the best	t of my knowledge.					
Approved	OCT 1	7 1997	_19 C	perator Tau	was Exploration USA					
	•		В	y Lo	un Charas					
Ву	ganny o	- Carlana		By Low Charas Tide Sr. Souse Operator						
Tide	Deputy Off	α Gas inspector		Date 10-3-97						
	_									

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

ur, date) ##

LAPSED TIME

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).