

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
720 South Colorado Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1750'FSL 890'FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Spudding/Csg. Report

5. LEASE  
SF-079508

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Cole A

9. WELL NO.  
1E

10. FIELD OR WILDCAT NAME  
Basin Dakota/Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 35; T28N; R10W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5889 gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/3/80 - 8/19/80

Spudded 12 1/4" hole 8/2/80. Drilled to 226'. Ran 5 jts. 9 5/8" 36# csg. Cmt with 200 sx CL-B and 2% CACL2. Plug down. Circ. to surface. Shoe at 219'. Reduced hole to 8 3/4". Continued drilling to TD of 6542' on 8/12/80. Ran 160 jts 7" 23# csg. Set at 6541' KB, DV tool 4588. Cmt. with 160 sx 50/50 POZ mix 6% gel. Tail in with 150 sx CL-B. Circ. out 2 BBLS mud flush. Cmt 2nd stage with 590 sx 50/50 POZ mix and 6% gel. Tail in w/150 sx CL-B. Pd 8/14/80 Released rig 8/14/80. TIH with bit, csg. Scraper, and 2 7/8" tbg. Tagged DV at 4590'. Drilled 9' cmt to PBD at 6493'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct Asst. Div.

SIGNED [Signature] TITLE Admin. Manager DATE 9/6/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

COPIES

MMCCC

\*See Instructions on Reverse Side

BY [Signature]