

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Tenneco Oil Company
3. ADDRESS OF OPERATOR  
720 S. Colo. Blvd., Denver, CO 80222
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1620' FSL 1750' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

- ☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Spudding/csg. report

5. LEASE S F 077035  
~~SF 07785~~
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Omler A
9. WELL NO.  
7E
10. FIELD OR WILDCAT NAME  
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 36, T28N, R10W
12. COUNTY OR PARISH San Juan 13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5937' gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/21/80

Spudded 12 1/4" hole 8/20/80. Circ. and cond. hole. Ran 6 jts. 9 5/8" 36# csg. set @ 259'. Cmt. w/225 sxs. CL-B & 2% CACL2. Reduced hole to 8 3/4" Ran 165 jts. of 7" 23# csg. set @ 6540 KB. 3 Stage cmt job: 1st stage; 120 sx 65/35 POZ mix, 6% gel, Tail in w/150 sx CL-B. 2nd stage; Tool @ 5408' 600 sx 65/35 POZ mix, 6% gel, Tail in w/150 sx CL-B. 3rd Stage; Tool @ 3436' 900 sx 65/35 POZ mix, 6% gel, Tail in w/225 sx CL-B. Circ 45 BBLS to pit. Set slips w/80,000#. Release rig @ 3:00 a.m., 9/4/80. Drilled out cmt. & DV tool @ 3428'. TIH and tagged 2nd stage DV @ 5401'. Drill out. TIH & tag fill @ 6433'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Charles W. Hines*

TITLE Asst. Div. Adm. Mgr.

DATE October 1, 1980

**ACCEPTED FOR RECORD**

(This space for Federal or State office use)

APPROVED BY 08 OCT 8 1980  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

BY

FARMINGTON DISTRICT