

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NOTES IN TRIPLICATE
(Other instructions on re-
verse side)

Budget Bureau No. 42-R1424

LEASE DENIGATION AND SERIAL NO.

NM 0764

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR Ladd Petroleum Corporation		7. UNIT AGREEMENT NAME	
3. ADDRESS OF OPERATOR 830 Denver Club Bldg. Denver, Colorado 80202		8. FARM OR LEASE NAME Knauff "B"	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 820' FSL 1660' FWL		9. WELL NO. I E	
14. PERMIT NO. 3/18/80		10. FIELD AND POOL, OR WILDCAT Fulcher Kutz	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5844 GR		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 31-28N-10W	
		12. COUNTY OR PARISH San Juan	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Spud & surface casing ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/16/80 Spud 8:AM Morrow Drilling. Cem. 13 3/8" 54.5# casing at 43' w/10 sx cement. Cement to surface. Complete 5:PM 4/16/80.

4/19/80 Spud 12 1/4" hole at 1:30 A.M. Four Corners Drilling Co. Recemented 13 3/8" with 70 sacks "B" + 3% CaCl. Good returns.

4-20/80 Cem. 8 5/8" 24# K-55 ST&C new casing at 893', with 500 sx "B" with 2% CaCl. Cem. circulated. P.D. 12 noon 4-20-80. Installed BOPE.

ACCEPTED FOR RECORD

JUN 3 1980

PERMISSION TO SIGN
BY *[Signature]*

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Drilling Manager

DATE 5/28/80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side