

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.
SF-046563

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR BRECK OPERATING CORPORATION	8. FARM OR LEASE NAME Kutz Government
3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod. Corp. P. O. Drawer 419 Farmington, New Mexico 87499	9. WELL NO. 4
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990'FNL, 990'FEL	10. FIELD AND POOL, OR WILDCAT Fulcher Kutz PC
14. PERMIT NO.	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Section 34-T28N-R10W N.M.P.M.
15. ELEVATIONS (Show whether DT, AT, GR, etc.) 5879'DF	12. COUNTY OR PARISH 13. STATE San Juan N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANT

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

COLLAPSE

REPAIRING WELL

ALTERING CASING

ABANDONMENT

XX

(Note: Report results of multiple completion or Well Completion or Recompletion Report and any other

17. DESCRIBE PROPOSED OR COMPLETED OPERATION: (Clearly state all pertinent details, and give pertinent data, including estimate of date of starting and proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all intervals and from pertinent to this work.) *

11/7/90: Ran 40 joints, 4-1/2", 10.50 Lb., K-55 casing (1749') with casing packer collar on bottom set at 1753'. Casing packer collar at 1751'. Cemented with 160 sacks Class "B" cement with 2.0% Calcium Chloride. Pump 50 sacks Class "B" cement with 2.0% Calcium Chloride from surface between 4-1/2" and 6-5/8" casing.

RECEIVED
JAN 4 1991
OIL CON. DIV
DIST. 3

FOR: BRECK OPERATING CORPORATION

18. I hereby certify that the foregoing is true and correct.

SIGNED

ORIGINAL SIGNED BY

EWELL N. WALSH

Ewell N. Walsh

TITLE

Agent

DATE

11/13/90

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 26 1990

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY