

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Supron Energy Corporation

3. ADDRESS OF OPERATOR

P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 955 Ft./South; 1725 Ft./East line

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO.

DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.

SF 047017 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Angel Peak

9. WELL NO.

23-E

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T. R., M., OR BLOCK AND SURVEY OR AREA

Sec. 10, T-28N, R-11W
N.M.P.M.12. COUNTY OR
PARISH
San Juan13. STATE
New Mexico

15. DATE SPUDDED 11/22/80 16. DATE T.D. REACHED 12/6/80 17. DATE COMPL. (Ready to prod.) 3/14/81 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 5522 R.K.B. 19. ELEV. CASINGHEAD 5511

20. TOTAL DEPTH, MD & TVD 6365 MD & TVD 21. PLUG, BACK T.D., MD & TVD 6310 MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* - - - 23. INTERVALS DRILLED BY - - - ROTARY TOOLS 0 - 6365 CABLE TOOLS - - -

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

6055 - 6203 Dakota (MD & TVD)

26. TYPE ELECTRIC AND OTHER LOGS RUN

Induction Electric and Compensated Density

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD
8-5/8"	24.00	266	12-1/4"	160 Sacks
4-1/2"	10.50	6354	7-7/8"	1280 Sacks (3 Stages)

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-3/8"EUE	6165	- - -

31. PERFORATION RECORDED (Interval, size and number)

1 - 0.42" hole at each of the following depths
6055, 56, 57, 77, 78, 79, 80, 81, 6136, 38,
6140, 42, 44, 46, 48, 50, 52, 54, 56, 58,
6160, 69, 70, 92, 93, 98, 6200, 02, 03.
Total of 29 holes.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6055 - 6203	2000 gal. 7-1/2% HCL, 120,000 lb. 20-40 sand, 1794 bbl. of 30 lb. Cross-linked gel. fluid. All fluid contained 2% KCL & biocide

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
		Flowing				Shut-In	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
3/14/81	3	3/4"	→		103		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
58	449	→		826			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

TEST WITNESSED BY

David Roark

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Kenneth E. Roddy
Kenneth E. Roddy

TITLE Production Superintendent

DATE

APR 2 1981
March 17, 1981

FARMINGTON DISTRICT

*(See Instructions and Spaces for Additional Data on Reverse Side)

BY

RB

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions. If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS			
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
				Ojo Alamo (Base)	560	
				Fruitland	1295	
				Pictured Cliffs	1615	
				Chacra	2595	
				Cliff House	3136	
				Point Lookout	3943	
				Gallup	5192	
				Greenhorn (Base)	6020	
				Dakota	6050	