(other) Ran 2-7/8" as Casing

PULL OR ALTER CASING

MULTIPLE COMPLETE **CHANGE ZONES** ABANDON*

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SF 047017 B 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Angel Peak "B"	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		
1. oil gas gy		
well well other 2. NAME OF OPERATOR	9. WELL NO. 30	
Supron Energy Corporation 3. ADDRESS OF OPERATOR P.O. Box 808, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790 Ft./N; 1800 Ft./E line AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH: Same as above	10. FIELD OR WILDCAT NAME Bloomfield Chacra Extension 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T-28N, R-11W, N.M.P.M. 12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 5793 R.K.B.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF		
REPAIR WELL	(NOTE: Report results of multiple completion or zone	

change on Form 9-330.)

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location	t dates,
measured and true vertical depths for all markers and zones pertinent to this work.)*	

- 1. Drilled 6-3/4" hole with mud to total depth of 3070 ft. R.K.B. Reached total depth on 11-17-80.
- Ran 98 joints of 2-7/8" E.U.E., 6.50# tubing as a casing string. Landed 2. at 3056 ft. R.K.B. Float collar at 3024 ft. R.K.B.

3. Cemented with 330 sacks of 65-35-6 with 12-1/2 lb. of Gilsonite per sack and 200 sacks of 50-50 poz mix with 2% gel. Plug down at 3:20 P.M. 11-18-80. Cement circulated to surface.

•	내 그는 소설 맞추는 다시다.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing/is true and correct	Set @ (1) Ft.
SIGNED Kenneth E. Roddy TITLE Production Supt. DATE	November 20, 1980
(This space for Federal or State office use)	
APPROVED BY TITLE DAT	Ε