

5 - USGS

1 - Flag Redfern

1 - File

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Flag-Redfern Oil Company

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1710' FSL - 790' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐


☐

☐

☐

☐

☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

See attached report, 11-7-80, for spud and surface casing.

See attached report, 11-11-80, for 2-7/8" csg.

Subsurface Safety Valve: Manufacturer and Type _____ Set @ _____ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Dugan TITLE Agent DATE 11-11-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:BY BL

NMCC



dugan production corp.

FLAG-REDFERN OIL CO.
Aloha #1
1710' FSL - 790' FWL
Sec 16 T28N R11W
San Juan County, NM

MORNING REPORT

- 11-7-80 MIRU Morrow Drlg. Co. Rig. Spudded 8-3/4" hole @ 10:30 a.m., 11-6-80. Drilled to 127'. Ran 3 jts 7" O.D., 23#, 8 Rd., ST&C "B" cond. csg. T.E. 123.76' set @ 125' G.L. cemented w/ 60 sx class "B". P.O.B. @ 2:00 p.m., 11-6-80. Good cement to surface. W.O.C.
- 11-8-80 Drlg. 5" hole @ 780'.
- 11-9-80 Drlg. 5" hole @ 1180'. Well kicked @ 960'). Mixed gel & starch - well is now completely under control. No mud properties available.
- 11-10-80 T.D. 1690'. Laying down drill pipe, prep to run 2-7/8" csg.
- 11-11-80 Laid down drill pipe. Ran 60 jts. 2-7/8" O.D. 6.4# CW55-10RD NEUE tbg for csg. T.E. 1692.51' set @ 1692' G.L. Had good circulation throughout job. Cemented w/ 75 sx extended slurry followed by 75 sx class "B" neat. Bumped plug w/ 1200 psi. Held OK. Shut in w/ 750 psi. Circulated trace of cement. P.O.B. 11:10 a.m. 11-10-80.