Form 9–331 Dec. 1973		Approved. et Bureau No. 42-R1424
UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM-01772-A	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTES	OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
reservoir. Use Form 9–331–C for such proposals	8. FARM OR LEASE NAME Reid	
1. oil gas well other DIST. 3  2. NAME OF OPERATOR	9. WELL NO. 21-E	
Southland Royalty Company  3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Basin Dakota/Undesignated Chacra	
P.O. Drawer 570, Farmington, New Mexico 87401  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
below.)	Section 19, T28N, R9W	
AT SURFACE: 1850' FSL & 790' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH San Juan	13. STATE New Mexico
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW	/ DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5865' GL	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Casing Report X  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	e all pertinent details, and	-330.)  I give pertinent dates,
1-14-82 Ran 158 joints (6667') of 5-1/2", 15.5# DV tools set at 4846' and 2300'. Cemer of Class "B" 50/50 Poz with 6% gel and lowed by 50 sacks of Class "B" Neat wit 1:00 A.M. 1-14-82. Cemented 2nd stage 50/50 Poz with 6% gel and 1/4# flocele of Class "B" Neat and 2% CaCl <sub>2</sub> . Plug of Cemented 3rd stage with 170 sacks of Cland 1/4# flocele per sack. Followed by 2% CaCl <sub>2</sub> . Plug down at 6:30 A.M. 1-14- temperature survey.	nted 1st stage wit 1/4# flocele per th 2% CaCl <sub>2</sub> , Plug with 285 sacks of per sack. Follow down at 4:00 A.M. lass "B" 50/50 Pozy 50 sacks of Clas	h 130 sacks sack. Fol- down at Class "B" ed by 50 sacks 1-14-82. with 6% gel s "B" Neat and
Subsurface Safety Valve: Manu. and Type	Set	t @ Ft.
18. Lhereby certify that the foregoing is true and correct		
SIGNED TITLE Drilling Cler  (This space for Federal or State off	rk DATE Januar	y 15, 1982
(This space for Federal or State off	ice use)	2705
APPROVED BY	DATE	irn ing KFRR
CONDITIONS OF APPROVAL, IF ANY:		N 2 0 1981

NMOCC