

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1750' FSL, 990' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
NOV 12 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF-079319

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Schwerdtfeger A

9. WELL NO.
1E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 36, T28N, R9W

12. COUNTY OR PARISH 13. STATE
San Juan NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5906 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/3/82: Ran GR/CCL. Perf Dakota @ 6436-40', 6564-74' w/2 JSPF (14', 28 holes), and @ 6464-90, 6600-14' w/ 1 JSPF (40', 40 holes). Estab rate w/1% KCL wtr. Acidize w/1400 gal 15% wtd HCL & 102 ball slrs. AIR 29 BPM @ 2,000 psi. ISIP 1050 psi. RIH w/junkbasket. Rec'd 101 balls. Frac dn csg w/80,000 gal 40# gel & 163,000# 20/40 SD. AIR 60 BPM & 2600 psi. ISIP 1850 psi. 15 min SI 1450 psi. SI overnight.
11/4/82: RIH w/tbg & sn 1 jt. Off btm. Tag sd @ 6508', CO to PBD. Land tbg @ 6543'. NDBOP, NUWH, Kicked well around w/N₂. Left FTCU.
11/4/82: RDMOSU.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Dennis Wilson TITLE Production Analyst DATE November 10, 1982

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

NMOCG

NOV 24 1982

*See Instructions on Reverse Side

BY

FARMINGTON DISTRICT

